

Quick release, dishwasher-safe, stainless steel with mesh grease filters ensure a clean, fresh kitchen.

Works with optional Universal Make-Up Air Dampers.

Model Numbers:



Brilliant halogen lighting provides work surface illumination.



Intuitive push-button controls operate speed and lights. Includes indicator for "ON."



Hood Sizes

| Width | 35-7/16" | |
|----------|-------------------------|--|
| Depth | 19-11/16" | |
| Finish | | |
| Stocked | Brushed Stainless Steel | |
| Features | | |

| Lighting Type | Halogen, G4-20W |
|-------------------------|--|
| Number of Lamps | 2 |
| Lighting Levels | 1 |
| Lighting Lamps Included | Yes |
| Control Type | 3-speed Pushbutton |
| Control Features | Heat Sentry™ |
| Remote Control | Not Available |
| Filter Type | Stainless Steel with Mesh Grease Filter |

Hood Blower Included (K3490)

| Internal | |
|------------|-----|
| Blower CFM | 500 |
| Sones | 9.5 |


Accessories

Non-ducted Capability

10' Flue Extension (Ducted) FEXTK34SS 10' Flue Extension (Non-ducted) FEXTK34SSN FILTERK3490CM Non-ducted Recirculating Kit CFM Reducer Kit Universal MUA Damper MD6TU, MD8TU, MD10TU

Installation Requirements

| Amps @ 120V | 3.2 |
|----------------------------|-------------|
| Electrical | Direct Wire |
| Duct Size: Internal Blower | 6" |
| Duct Direction | Vertical |
| Backdraft Damper | Included |



Installation height above the cooking surface:

8' ceiling: 24" 9' ceiling: 24"–30" 10' ceiling: 26"–30"

Telescopic flue for 8'-9' ceiling is standard. Optional flue extensions for 10' ceiling

For more details see the product specifications sheet found at www.BESTRangeHoods.com