Indoor | Beverage Center 24" ADA / Glass Door Refrigerator

- Ada height compliant, installs under 34" countertop
- Signature Blue interior
- Full wrapped stainless-steel exterior
- Articulating, concealed self-closing hinges with built-in door stop
- Low e, argon gas-filled triple-paned tempered glass door with uv coating•
 Multifunction capacitative touch electronic control
- Temperature range: 34°F to 65°F
- Fan-assisted cooling system allows for even temperatures, quicker cooldown times, and added efficiency
- Full-length flush LED theater lighting can be set to display your collection for 4 or 6 hours or schedule nightlight feature
- Adaptable racking system includes 3 stainless front, full-extension racks with 3 chrome-plated wire shelves and 1 gray vinyl-clad wine rack insert. Optional shelf inserts include gray vinyl-clad wine rack inserts and/or tempered glass shelf inserts making it easy to adapt to food and beverage storage needs
- Clear bottom crisper drawer
- Volume of 4.7 Cubic feet
- Unit ships right hinged with field-reversible doors
- Stainless model includes 1" diameter stainless steel handle with faceted standoffs (24" length)
- Panel ready model requires 3/4" custom door panel and handle
- Precise zero clearance design allows for unmatched integration into any built-in setting
- 4 Independent adaptable leveling legs
- Adaptable grille accepts an integrated toe kick and allows front/back and up/down alignment with adjacent cabinetry and toe kick/plinth
- Automatic defrost
- Lock standard
- Product volume 4.7 cubic feet





Model Details

Model	Lock	Finish	Description	Shipping Weight
YPBEV24-SS-ADA	No	Stainless Steel	24" ADA Bev Center / Glass Door Refrigerator	162-169 lbs

Refer to page 53 for accessories

Dimensions/Weight	Detail
Product Depth	23 1/4"
Product Height	32" – 33"
Product Width	23 7/8"
Product Weight	140 lbs
Product Volume	5.1 cu ft
Shipping Dimensions	26 ³ / ₄ " x 27 ¹ / ₂ " x 36 ³ / ₄ "
Shipping Weight	162-169 lbs

Integration/Panel Information*	Detail
Panel Height	28" – 29"
Panel Thickness	3/4"
Panel Width	23 5/8"

^{*}Refer to manual for all panel dimensions and installation instructions









Model	Details
Control Type	Electronic Capacitative Touch with OLED Screen
Indoor or Outdoor	Indoor
Built-in Installation	Inset, Frameless / Overlay and Framed Cabinet Styles
Refrigerant Type	R600a

Electrical	Details
Electrical Requirements	115 V / 60 Hz
Volt Range	104 V ~ 127 V
Maximum Amp Fuse	15 amp
Amps Running	0.7 amps

Approvals – Certifications	Details
ETL Residential / Commercial	Yes
ETL Sanitation	Yes
Star K	Yes





*Dimensions are the same for Panel Ready unit when $^{3}\mbox{\sc 4}''$ panel applied

