General Features

Anti-fingerprint stainless Yes

500 Series - Stainless Steel B36FD52SNS



B36FD52SNS Stainless Steel

Also available in:

Black Stainless Steel B36FD52SNB

36" 500 Series French Door Bottom Freezer Refrigerator, Standard Depth, External Ice/Water Dispenser, Stainless Steel, Bar Handles

Features & Benefits

Never run out of ice – the QuickIce Pro* System produces 12 lbs. of ice per day.1

Say goodbye to smudges and fingerprints with new anti-fingerprint stainless steel

Convenient external control panel displays fridge and freezer temperature settings

With Home Connect*, remotely control and monitor your appliance to efficiently manage your day.

UltraClarityPro® water filter reduces >99.9% of sediment that may be found in your water and ice, including harsh elements like chlorine and chloramine.

Dimensions and Weight	
Overall width (inches)	35 5/8"
Overall height (inches)	70"
Overall depth with doors and handles (inches)	32 1/8"
Overall depth without doors and handles (inches)	28 3/8"
Required cutout size (HxWxD) (inches)	70" x 36" x 25"
Net Weight /Gross Weight (approx.) (lbs.)	327 / 355
Style	
Color	Stainless Steel
Door handle type	Bar handle
Interior finish	White and stainless steel back wall
Standard depth	Yes
Performance	
VitaFresh® Plus	Yes
SuperFreeze®	Yes
Evaporators / Compressors	1 / 1
QuickIce Pro®	Yes
Automatic defrosting	Yes
External water dispenser	Yes (ice and water)
One touch bottle fill	Yes
Capacity and Storage	
Total capacity (cu. ft.)	26
Refrigerator capacity (cu. ft.)	18
Freezer capacity (cu. ft.)	8
Full-extension freezer storage drawer	1
2-tiered freezer drawer	Yes
Full width chiller drawer	1
Humidity control drawers	2
Storage shelves	4 Adjustable, 1 Fixed
Small door bins	5
Large gallon door bins	2

steel	
External control panel	Yes
Water filter replacement indicator	Yes
Water filter	UltraClarityPro®
Ice maker	Yes
Ice production (24 hrs.), ice cubes (Ibs.)	12
Ice storage capacity (lbs.)	2.8
LED interior and drawer lighting	Yes
Independent cooling systems	1
Cooling system	MultiAirFlow™
AirFresh® filter	Yes
Maximum sound level	40 dBA
Wi-Fi-enabled for control with Home Connect® app	Yes
Energy Efficiency	
Energy consumption (kWh/yr)	702
ENERGY STAR® Certified	Yes
Technical Specs	
	110-127 V, 60 Hz,
Required power supply	15 amps
Required power supply Plug type	
	15 amps
Plug type	15 amps 120V-3 Prong
Plug type Power cord length (in.)	15 amps 120V-3 Prong 91"
Plug type Power cord length (in.) Operating Temperature	15 amps 120V-3 Prong 91" o 43°F (6°C)
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C)
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t Freezer Drawer: -7°F (-22°	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C) or approx. 8 Hrs.
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t Freezer Drawer: -7°F (-22°C) SuperCool: 30°F (-1°C) for	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C) or approx. 8 Hrs.
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t Freezer Drawer: -7°F (-22° SuperCool: 30°F (-1°C) for SuperFreeze®: -15°F (-26°	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C) or approx. 8 Hrs.
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t Freezer Drawer: -7°F (-22° SuperCool: 30°F (-1°C) fo SuperFreeze*: -15°F (-26° Warranty Limited warranty, parts	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C) or approx. 8 Hrs. C) for approx. 8 Hrs.
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t Freezer Drawer: -7°F (-22° SuperCool: 30°F (-1°C) for SuperFreeze®: -15°F (-26° Warranty Limited warranty, parts & labor	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C) or approx. 8 Hrs. C) for approx. 8 Hrs.
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t Freezer Drawer: -7°F (-22° SuperCool: 30°F (-1°C) fo SuperFreeze*: -15°F (-26° Warranty Limited warranty, parts & labor Optional Accessories Replacement UltraClarity	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C) or approx. 8 Hrs. C) for approx. 8 Hrs. 1 Year
Plug type Power cord length (in.) Operating Temperature Refrigerator: 33°F (1°C) t Freezer Drawer: -7°F (-22° SuperCool: 30°F (-1°C) fo SuperFreeze®: -15°F (-26° Warranty Limited warranty, parts & labor Optional Accessories Replacement UltraClarityl BORPLFTR55	15 amps 120V-3 Prong 91" o 43°F (6°C) °C) to 6°F (-14°C) or approx. 8 Hrs. C) for approx. 8 Hrs. 1 Year Pro° water filter: ilter Kit: FPETHKT50

90 degree door stopper: 10012733








36" Standard-Depth 3-Door Refrigerator




500 Series - Stainless Steel B36FD52SNS


Installation Details



A: Add 5/8" (17) with front leveling feet fully extended


B: Add 1" (25) for fixed spacers on back






A: Add 5/8" (17) with front leveling feet fully extended


Measurements in inches (mm)



Drawers can be pulled out with door open to 90° Drawers can be taken out with door completely opened

measurements in inches (mm)





Leave 1/2" (12.7) gap at the top and 1" (25.4) behind the refrigerator for proper ventilation.

It is recommended that you do not install the refrigerator near a heat source such as a stove or a range.

measurements in inches (mm)

Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST). Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout.

Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.