



#### Color Variants

**CM450130**  
Aluminium-backed glass frontage  
Width 60 cm  
**CM450110**  
stainless steel-backed glass frontage  
Width 60 cm

#### Included accessories

1 x measuring spoon.  
1 x assembly screws.  
1 x milk container.  
1 x test strip.  
1 x connection hose for milk frother.

**CM450130**  
Fully automatic espresso machine 400 series  
Aluminium-backed glass frontage  
Width 60 cm  
Controls at the top

Continuous flow heater means no waiting time and constant brewing temperature  
Aroma brewing technology for a full aroma  
Single portion cleaning  
TFT touch display  
One-touch operation  
Personalisation function  
Seven light settings

#### Type of beverage

Espresso / 2 x Espresso.  
Coffee / 2 x Coffee.  
White coffee.  
Latte macchiato.  
Cappuccino.  
Milk froth.  
Warm milk.  
Hot water.

#### Handling

Rotary knob and TFT touch display operation.  
Clear text display in 25 languages.  
Personalisation function, up to 8 beverages can be personalised and memorised.  
3 beverage size settings; can be individually adjusted to match the size of the cup.  
5 coffee strength levels from mild to extra strong.  
3 coffee and hot water temperature levels.  
4 grinding level settings.  
Height-adjustable coffee dispenser up to 15 cm.  
Automatic slide-out function.

#### Features

Grinding unit with ceramic discs.  
Separate container for second ground coffee type.  
Water pump with 19 bar pressure.  
Double grinding and brewing cycles for extra intensity for one beverage.  
Double grinding and brewing cycles for two beverages.  
Dispenser with integrated milk system.  
Insulated milk container for up to 0.7 litres.  
Integrated lighting with 3 LEDs.  
Bean container for 1 kg.  
Automatic adjustment of ground coffee quantity.  
Removable 2.5 litre water tank.  
Electronic fill level control for coffee beans and water.  
Electronic water filter exchange indicator.  
Electronic fill level control for drip tray and container for coffee dregs.

#### Safety

Child lock.  
Safety shut-off.

#### Cleaning

Fully automatic rinse programme when machine is turned on/off.  
Automatic quick rinsing of milk system.  
Automatic cleaning and descaling programme.  
Removable brewing unit.  
Coffee dregs container and drip tray dishwasher-safe.  
Milk frother dishwasher-safe.

#### Planning notes

Ideal installation height 95 cm (top edge of niche bottom), max. 120 cm.  
The façade of the appliance extends 47 mm from the furniture cavity.

#### Characteristics

Built-in / Free-standing  
Frothing nozzle  
Yes  
Display  
Water protection system  
no  
Portion sizes  
All cups  
Dimensions of the product (mm)  
455 x 590 x 562  
Dimensions of the packed product (HxWxD) (mm)  
540 x 620 x 670  
Required niche size for installation (HxWxD)  
450 x 564 x 514  
Hot water spout  
Yes  
Adjustable programs  
Standby function  
No  
Pump pressure (bar)  
19  
Simultaneous preparation of 2 cups  
Yes  
Included accessories  
1 x measuring spoon, 1 x assembly screws, 1 x milk container, 1 x test strip, 1 x connection hose for milk frother  
Optional accessories

#### Consumption and connection features

Electrical connection rating (W)  
1700  
Current (A)  
10  
Voltage (V)  
220-240  
Frequency (Hz)  
50/60  
Plug type  
Gardy plug w/ earthing  
Product group  
Built-in coffee machine  
Brand  
Gaggenau  
Product name/family  
Product name / Commercial code  
CM450130  
Universal Product Code  
825225915195  
Main colour of product  
Alu  
Typology  
Fully automatic  
Approval certificates  
CE, ROSTEST, VDE  
Length electrical supply cord (cm)  
150.0  
Length of electrical supply cord (in)  
Recommened height for installation (in)  
Recommened height for installation (mm)  
450  
Appliance Dimensions (h x w x d) (in)  
Dimensions of the product (mm)  
455 x 590 x 562  
Dimensions of the packed product (in)  
Dimensions of the pallet (in)  
Dimensions of the packed product (HxWxD) (mm)  
540 x 620 x 670  
Net weight (lbs)  
54  
Net weight (kg)  
24.66  
Gross weight (lbs)  
60  
Gross weight (kg)  
27.30  
Capacity water container  
2.5  
2017-07-12  
Page 1

When installing in a corner a side clearance of 200 mm is required.  
Installation directly above 14 cm high WS in 59 cm standardised niche.  
Special accessories (order as spare parts):  
Part No. 467873 Water-filter cartridge  
Part No. 311138 Descaling agent  
Part No. 310575 Cleaning tablets

#### Connection

Total connected load 1.70 kW.  
Connection cable 1.5 m with plug.

