

# ARS23MLLH



83.75" x 27.5" x 31" (H x W x D)

Performance series Pharma-Lab 23 cu.ft. all-refrigerator in stainless steel with left hand door swing

**Highlights:**

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout

Additional sensor reads interior air temperature for superior temperature control

**Product Features:**

|   |   |
|---|---|
| Purpose-built design                            | Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions   |
| Adjustable temperature                          | Interior is pre-set to 5°C, with an adjustable control range from 2 to 10°C   |
| Temperature alarm                               | Visual and audible alarms alert if the interior temperature rises or falls out of set range   |
| Complete stainless steel construction           | Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup   |
| Forced air cooling                              | Top-mounted commercial fan ensures rapid temperature recovery   |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup  |
| Self-closing door                               | Closes to save energy but will remain open when the door is opened at a 90° angle for easier loading  |
| Open door alarm                                 | Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will sound continuously if the door is open for more than 5 minutes |
| 6 inch casters                                  | Ships with a set of casters (2 locking) for optional user installation  |

## ARS23MLLH Specifications:

| Overview                   |                     |
|----------------------------|---------------------|
| Height of Cabinet          | 83.75" (213 cm)     |
| Width                      | 27.5" (70 cm)       |
| Depth                      | 31.0" (79 cm)       |
| Depth with Handle          | 32.75" (83 cm)      |
| Depth with door at 90°     | 56.5" (144 cm)      |
| Capacity                   | 23.0 cu.ft. (651 L) |
| Defrost Type               | Automatic           |
| Door                       | Stainless Steel     |
| Cabinet                    | Stainless Steel     |
| US Electrical Safety       | UL                  |
| Canadian Electrical Safety | ULC                 |
| Sanitation                 | ETL-S               |
| Amps                       | 7.5                 |
| Voltage/Frequency          | 115 V AC/60 Hz      |
| Weight                     | 282.0 lbs. (128 kg) |
| Shipping Weight            | 292.0 lbs. (132 kg) |
| Parts & Labor Warranty     | 2 Years             |
| Compressor Warranty        | 5 Years             |
| Refrigerator Features      |                     |
| Door Swing                 | LHD                 |
| Reversible                 | No                  |
| Shelf Type                 | Wire                |
| Shelf Qty                  | 4                   |
| Adjustable Shelves         | Yes                 |
| Thermostat Type            | Digital             |
| Fan Type                   | Interior            |
| Refrigerant Type           | R290a               |
| Refrigerant Amount         | 2.5oz.              |
| High Side PSI              | 290.0               |
| Low Side PSI               | 155.0               |
| Wheel Qty                  | 4                   |
| Interior Light             | Yes                 |
| Temperature Range          | 2 to 10°C           |
| Dimensions                 |                     |
| Interior Height            | 51.5" (131 cm)      |
| Interior Width             | 23.5" (60 cm)       |

Interior Depth

27.0"



