30 205

GROHE ZEDRA

SINGLE-HANDLE PULL DOWN KITCHEN FAUCET TRIPLE SPRAY 1.75 GPM WITH TOUCH TECHNOLOGY

Pure Freude an Wasser

GROHE

STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- 16" Faucet height
- 8 9/16" Aerator height
- 9 3/16" Faucet reach
- Touch activation of water via skin contact
- 6 V lithium-battery supply (type CR-P2)
- CE approved and meets the requirements of IAPMO IGC 349-2017
- Automatic safety stop after 60 sec. (factory set)
- Pull-down spray with 3 spray types: laminar spray, shower spray, and blade spray (reduced water consumption by up to 50% and even stronger spray performance)
- Stop function - pause button to stop the water flow
- Automatic return to laminar spray
- Adjustable flow rate limiter
- 360° Swivel spout
- Nylon braided flex hoses
- Quick installation system
- 1.75gpm
- GROHE Zedra is the new name for Ladylux L2



PRODUCT FEATURES:

- GROHE SilkMove®
- GROHE StarLight®
- GROHE QuickFix®

CERTIFICATIONS:

- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

AVAILABLE FINISHES:

30205002	GROHE StarLight® Chrome
30205DC2	SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.630.582.7711 Fax: 1.630.582.7722
We reserve the right to make revisions without notice to product specifications.
For the most current Specification Sheet, go to www.grohe.us.
08-04-2021

PART OF LIXIL

30 205

GROHE ZEDRA

SINGLE-HANDLE PULL DOWN KITCHEN FAUCET TRIPLE SPRAY 1.75 GPM WITH TOUCH TECHNOLOGY

Pure Freude an Wasser

TECHNICAL DATA:

Product Height	**16 in**
Product Length	**10-1/16 in**
Product Width	**6-5/16 in**
Fitting Spout Height	**8-9/16 in**
Fitting Spout Reach	**9-3/16 in**
GPM (Min)-GPM (Max)	**1.75 gal (US)/min**
Fitting No of Holes Required	**1**

