

SPECIFICATIONS

INPUTS

Preamp Inputs: 3 (6 channels)
Input Impedance: 20k Ω

OUTPUTS

Preamp Outputs: 3 (6 channels)
Maximum Output Level: 7.5Vrms
Output Gain: $\pm$ 12dB
Output Impedance: 150 Ω

PERFORMANCE

Total Harmonic Distortion: 0.01%
Frequency Response: 10Hz-22kHz
Equalizer Frequencies (front/rear): 125Hz, 175Hz, 250Hz, 500Hz, 1kHz, 2kHz, 8kHz
Equalizer Frequencies (sub): 31.5Hz, 40Hz, 50Hz, 63Hz, 80Hz, 100Hz, 125Hz
PFM Frequency: 20Hz or 30Hz selectable
Crossover Frequency: 50Hz-500Hz selectable
Crossover Type: 24dB/Octave Linkwitz-Riley
Signal Delay Max (Left/Right): 10ms
Signal Delay Max (Front/Sub): 35ms

CONTROL

Remote In
12VDC Remote Out (always active when unit is on)

GENERAL

Power Supply: High Headroom PWM Switching
Current Draw: 350mA
Recommended Fuse Rating: 2A

WEIGHTS & DIMENSIONS

Dimensions: 9.25"W x 5.75"D x 1.25"H
Weight: 3.0lbs (1.4kg)

IN THE BOX: DQDX, [ACR-3 Remote](#), [Power and Speaker Connectors](#), Manual, Warranty