

Product data sheet

CONSTRUCTION TYPE

Stackable	•
Side-by-side	•
Slot-in	•
Door hinging	left

TYPE

Product brand	W1 White Edition
Front loader	•

SPIN

Max. spin speed	1600
Rinse hold	•
“Without spin” function	•

DESIGN

Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Lotus white with chrome ring
Colours of selector dials	Lotus White / Chrome ring
Control panel version	5° incline
Control type	Rotary selector

Display

ComfortSensor white, 1 line

CLEANING PERFORMANCE

Innovative IntenseWash technology	•
Proven virus hygiene	•
TwinDos automatic dispensing of detergent	•
CapDosing portioned dispensing	•

GENTLE LAUNDRY CARE

Honeycomb drum	•
Load in kg	18 (8.0)

USER CONVENIENCE

AddLoad	•
Networking with Miele@home	•
Delay start up to 24 h	•
Time left display	•
Program sequence indicator	•
Drum lighting	LED
Language Options	•
AutoClean detergent drawer	•

EFFICIENCY AND SUSTAINABILITY

Hot-water connection	•
EcoFeedback	•
Low-temperature washing “cold” and “20°C”	•

Automatic load recognition	•
Flow meter	•
Foam sensing	•
ProfiEco motor	•

WASH PROGRAMS

Normal	•
Wrinkle-free	•
Sanitize	•
Handwash	•
Dress Shirts	•
Extra White	•
Darks/Denims	•
QuickIntenseWash	•
Table Linen/Drapes	•
Sportswear	•
Woollens	•
Silks	•
Drain/Spin	•
Quick Rinse	•
Baby Clothes	•
Towels	•
Downs	•
Pillows	•
Delicates	•
Express	•
Outdoor	•
Proofing	•

Clean Machine

•

EXTRA OPTIONS

SingleWash

•

AllergoWash

•

Soak

•

Prewash

•

SoftSteam

•

Soiling level selection

•

QUALITY

Counterweights made of cast iron

•

SAFETY

Child lock

•

PIN code

•

Optical interface

•

Water protection system

Watercontrol-System

Water protection system

Water Control System

TECHNICAL DATA

Dimensions in mm (width)

23 1/2 (596)

Dimensions in mm (height)

33 1/2 (850)

Dimensions in mm (depth)

25 3/8 (643)

Appliance depth with door open in mm

42 1/2 (1077)

Weight in lbs (kg)

212 (96)

10/16/23, 8:45 AM

WXI860 WCS TDos & IntenseWash | Miele

Total rated load in kW	1.300
Voltage in V	120
Fuse rating in A	15
Frequency in Hz	60
Length of power cable in m	6 (2)
Dimensions (H x W x D) in mm	33 1/2 (850)x23 1/2 (596) x25 3/8 (643)

ACCESSORIES SUPPLIED

3 caps	•
UltraPhase 1 + 2	•