



#### Color Variants

RF463703  
Fully integrated appliance  
Width 24" (61 cm)

#### Optional accessories

RA450000  
Mechanical particle filter  
RA450010  
Activated charcoal filter for water filter system including saturation indicator

#### Required installation accessories

RA460010  
Additional side heating element

#### Installation Accessories

RA422610  
Stainless steel door panel with handle  
RA425110  
Long stainless steel door handle  
RA460020  
Connecting element for vertically split appliance fronts (for a flush front)  
RA460040  
Finger protection for extra long furniture fronts  
RA461615  
Ventilation grill, stainless steel

RF463703

Freezer column

Fully integrated appliance

Width 24" (61 cm)

Left-hinged

Width 24" (61 cm)  
Stainless steel interior  
Integrated automatic ice maker with fixed water connection  
Illuminated dispenser for ice cubes, crushed ice and chilled water  
Solid aluminum door bins  
Net volume 320 litres

#### Operation

Electronic precision temperature control with digital temperature display.

#### Technical features

Dynamic cool air distribution with Multi-Flow Air System.  
Automatic defrosting with defrost water evaporation.  
Energy-saving vacation mode.  
Open-door and malfunction warning system.

#### Freezer compartment

No-frost technology with fast freezing.  
Temperature adjustable from 7 °F to -9 °F (-14 °C to -25 °C).  
4 solid metal shelves, two of which are manually adjustable.  
2 fully extendable drawers with transparent front, one of which is large, one is regular.  
Bright interior lighting with LED sidewall pillars.  
One gallon door bin.  
1 door bin with transparent front flap.

#### Ice and water dispenser

Illuminated ice and water dispenser.  
Integrated, with fixed water connection.  
Ice maker can be switched off independently.  
Ice cube production approx. 4.2 lb (1.9 kg)/24 h.  
Ice cubes and crushed ice.  
Removable ice storage bin with approx. 6.6 lb (3 kg) capacity.  
Chilled water supply approximately 1.3 quarts.

#### Planning notes

Flat hinge.  
Door opening angle of 115°, optional 90° door stop.  
Max. door panel weight 126 lb.  
Shut-off valve for water connection must be planned next to the appliance and always be accessible.  
If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.  
Cold water connection required.  
Electrical location 6" above ground in lower left corner of unit.  
Water pressure 29 to 116 psi.

#### Consumption data

Energy consumption 1.353 kwh/24 h.  
Energy consumption 493.85 kwh/year.  
Noise level 39 dB.

#### Rating

Total rating 0.565 kW.  
Total Amps: 10 A.  
120 V / 60 Hz  
Connecting cable 139 1/3" with plug.  
Supply hose 118" with 3/4" connection.

#### Product Features

Multi-Flow Air Tower  
Yes  
Number of compressors  
1  
Number of independent cooling systems  
1  
Eco Mode  
Yes  
SUPERFREEZE  
Yes  
Number of Door Bins - Freezer  
2  
Adjustable Door Bins - Freezer  
No  
Tilt-Out Door Bins - Freezer  
Yes  
Number of Shelves - Freezer  
2  
Adjustable Door Bins - Freezer  
No  
Shelf Material - Freezer  
Metal  
Door Hinge  
Left  
Reversible Door Hinge  
No

#### Consumption and connection features

UPC code  
825225900344  
Variant color  
Panel ready  
Installation Type  
N/A  
Silence level (dBA)  
39  
Watts (W)  
565  
Current (A)  
10  
Volts (V)  
120  
Frequency (Hz)  
60  
Total annual energy consumption (kWh)  
493.8  
Energy Star® qualified  
Yes  
Approval certificates  
ETL, ETL C  
Power Cord Length  
139 1/3"  
Plug type  
120V-3 prong  
Appliance dimensions (h x w x d) inch  
83 3/4 " x 23 3/4 " x 24"  
Required cutout size (HxWxD) (in)  
x 84" x 23 3/4 "  
Appliance Width (in)  
23 3/4 "  
Height (in)  
83 3/4 "  
Depth (in)  
24"  
Product packaging dimensions (HxWxD) (in)  
88.97 x 27.55 x 29.52  
Total unit gross capacity (cu. ft.) - AHAM  
11  
Net weight (lbs)  
355  
Gross weight (lbs)  
386  
2017-08-24  
Page 1

# GAGGENAU

