

# SBC7BRSIFCM2LHD



#### 33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved cold brew/nitro dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes panel-ready door, adjustable legs, and caster set for optional mobility

#### **Highlights:**

Made in Europe

Dual tap system lets you serve both regular cold brew and nitro coffee

Panel-ready door lets you customize the unit to best match your style

### **Product Features:**

24" Wide Cold Brew/Nitro Coffee Dispenser Kegerator includes all of the equipment you need to serve cold brew and nitro coffee from two sixtel or Cornelius kegs Made in Europe & the USA Refrigeration unit is constructed in Europe and designed and modified in the USA Versatile use Approved for both residential and commercial settings Commercially listed ETL-S listed to ANSI-NSF Standard 7 for commercial use Panel-ready door Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.) Dispenses both flat and nitro coffee Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts Complete cold brew tap kit included Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs Dual tap system Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs Slim counter height dimensions for recessed Ideal 24" footprint for an easy fit or freestanding use SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified

770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799

info@summitappliance.com





## SBC7BRSIFCM2LHD Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	22.38" (57 cm)
Depth with door at 90°	44.25" (112 cm)
Capacity	5.3 cu.ft. (150 L)
Defrost Type	Automatic
Door	Integrated Frame
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	293.0kWh/year
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	121.0 lbs. (55 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101106311
Kegerator	
Kegerator Door Swing	LHD
-	LHD Yes
Door Swing	
Door Swing Reversible	Yes
Door Swing Reversible Height Adjustable	Yes Yes
Door Swing Reversible Height Adjustable Tap Kit	Yes Yes Yes
Door Swing Reversible Height Adjustable Tap Kit Number of Taps	Yes Yes Yes 2
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves	Yes Yes Yes 2 Yes Glass and
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type	Yes Yes Yes 2 Yes Glass and Scalloped
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty	Yes Yes Yes 2 Yes Glass and Scalloped 4
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type	Yes Yes Yes 2 Yes Glass and Scalloped 4 Dial
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light	Yes Yes Yes 2 Yes Glass and Scalloped 4 Dial Yes
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light Refrigerant	Yes Yes Yes 2 Yes Glass and Scalloped 4 Dial Yes R600a
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light Refrigerant Amount	Yes Yes Yes 2 Yes Glass and Scalloped 4 Dial Yes R600a 0.64 oz.
Door Swing Reversible Height Adjustable Tap Kit Number of Taps Adjustable Shelves Shelf Type Shelf Qty Thermostat Type Interior Light Refrigerant Refrigerant Amount Inter Height	Yes Yes Yes 2 Yes Glass and Scalloped 4 Dial Yes R600a 0.64 oz. 27.75" (70 cm)

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	6.0" (15 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	36 to 46°F



