

EAN: 4002516229070 / Material number: 11204470 /

PWM 908 [EL DP-1]

Professional washing machine, Little Giants, electric heating, drain pump and short program cycle times and programs specific to the target group.



- Drum volume 2.58 (73) ft³ (I), load size 20 (9.0) lb (kg)
- 22% less water consumption and 28% less energy consumption*
- Tested for intensive use unique Miele quality
- Top convenience with full-touch color display M Touch Flex
- Thorough cleaning with professional washing programs
- * Based on the Cottons program with a hot water connection, compared to the predecessor model.

| Construction type and design | |
|--|-------------------------|
| Design | Front-loader, stackable |
| Product line | Performance Plus |
| Front | Stainless Steel |
| Control panel color | Stainless Steel |
| Load in lbs | 20 (9.0) |
| Drum volume in cubic feet (I) | 2.58 (73) |
| Door opening [Ø] in in.(mm) | 11 13/16 (300) |
| Door opening angle in degrees | 167 |
| Door hinging | right |
| Maintenance-free synchronous motor | • |
| Honeycomb drum with perforated rear wall made of stainless steel | • |
| Application | |
| Suitable for hotels and restaurants | • |
| Suitable for senior living facilities | • |
| Suitable for launderettes | • |
| Suitable for residential homes and apartments | • |
| Suitable for dry cleaners | • |
| Suitable for commercial laundries | • |
| Suitable for small businesses | • |
| Suitable for universities, nurseries, and schools | • |
| Suitable for hospitals | • |
| Suitable for camp sites | • |
| Suitable for sports clubs | • |
| Suitable for beauty salons, spas, and fitness centers | • |
| Suitable for doctors' and dentists' practices | • |
| Suitable for the petrochemical industry | • |
| Suitable for the food-processing industry | • |
| Suitable for amusement parks and holiday complexes | • |
| Suitable for public/community care facilities | • |
| Performance data | |
| Tested virucidal efficacy | • |
| Certified hygiene | • |
| Specific water consumption for cold water connection in I/ kg | 6.10 |
| Specific energy consumption for cold water connection in kWh/lb | 0.12 |
| Specific water consumption for hot water connection in I/ kg | 5.80 |
| Specific energy consumption for hot water connection in kWh/lb | 0.06 |
| Water consumption for cold water connection in l | 55.0 |
| Energy consumption for cold water connection in kWh | 1.10 |
| Program duration in minutes with cold water connection | 59 |
| Water consumption for hot water connection in I | 52.0 |
| Energy consumption for hot water connection in kW | 0.57 |
| Program duration in minutes with hot water connection | 49 |
| Residual moisture with cold rinse in $\%$ | 48 |



PWM 908 [EL DP-1]

Professional washing machine, Little Giants, electric heating, drain pump and short program cycle times and programs specific to the target group.



| Residual moisture with hot rinse in $\%$ | 45 |
|--|-----------------------------------|
| Spin speed in rpm | 1600 |
| g factor | 704 |
| Tested operating hours | 30000 |
| Control | |
| Control system | M Touch Flex |
| Programmability | programmable |
| Max. delay start in h | 96 |
| Countdown indicator | • |
| Program sequence indicator | • |
| Language can be selected easily at any time | • |
| Dispensing | |
| Detergent dispenser drawer | 3 compartments |
| CapDosing | • |
| Flexible dispensing adapter (option) | • |
| Maximum number of connections for liquid dispenser pumps [number] | 6 |
| Empty sensor | • |
| Standard electrical connection | |
| Type of heating | Electric |
| Electrical connection | 2~208-240V 60HZ |
| Heater rating in kW | 3.80-5.00 |
| Total connected load in kW | 4.00-5.20 |
| Fuse rating in A | 30 |
| NEMA plug: Twist Lock L6-30 | • |
| Water connection/drainage | |
| Cold water [number] | 1x 1/2" hose w/ 3/4" th. union |
| Hot water [number] | 1x 1/2" hose w/ 3/4" th. union |
| Drain pump | DN 22 |
| Dimensions and weight | |
| External dimensions, net height in inches | 33 1/2 (850) |
| External dimensions, net width in inches | 23 7/8 (605) |
| External dimensions, net depth in inches | 28 1/8 (714) |
| External dimensions, gross height in inches | 37 1/16 (940) |
| External dimensions, gross width in inches | 26 (660) |
| External dimensions, gross depth in inches | 30 1/4 (768) |
| Net weight in lbs.(kg) | 230 (104.0) |
| Gross weight in Ibs. | 239 (108) |
| Maximum floor load in N | 2820 |
| Emission values | |
| Emissions – sound pressure at workplace | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 1.00 |
| Features | |
| 3-dimensional imbalance monitoring | • |
| Commercial shock absorber | • |
| Hard-wearing stainless-steel flange | • |
| Disinfection rinse | • |



PWM 908 [EL DP-1]

Professional washing machine, Little Giants, electric heating, drain pump and short program cycle times and programs specific to the target group.



| EAN: 4002516229070 / Material number: 112044 ⁻ | 70 / |
|---|------|
| Old Material Number: 51908359NAM | |
| EcoSpeed | • |
| SoftSteam | • |
| Efficient rib technology | • |
| Temperature monitoring | • |
| Special heater element | • |
| Automatic load control | • |
| Volumetric flow meter | • |
| LED drum lighting, class 1 | • |
| Communication slot | • |
| Add laundry | • |
| Appliance-independent accessories | • |
| Efficiency and sustainability | |
| Recycling rate in % | 95 |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| WiFi Conn@ct | • |
| Standards, test certificates, and symbols | |
| CE | • |
| Splash protection IPX4 | • |
| WEEE | • |