Power Pack for Crestron[®] Shade Interfaces & Roller Shade Motors



MODELS

Available Models

CSA-PWS40: Power Pack for Crestron[®] Shade Interfaces & Roller Shade Motors

Notes:

 The CSA-PWS40 only provides power to compatible Crestron roller shade motors. Cresnet[®] control wiring must come from a different source, if needed.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative in your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, Crestron logo, Cresnet, and infiNET EX are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

The Crestron[®] CSA-PWS40 is a wall-mounted 40 Watt, 24 Volt regulated power pack that provides power for a Crestron shade interface, model CSC-DCCN or CSC-DCEX (both sold separately).

In addition, the CSA-PWS40 can provide local power for one Crestron roller shade motor, such as the CSM-QMT50 and CSM-QMTDC-256-2, via a direct connection to the motor's pigtail^[1]. This is especially useful in situations where an infiNET EX[®] wireless network is employed.

SPECIFICATIONS

Load Ratings

Output: 40 Watts (1.67 Amps) @ 24 Volts DC Regulated Ripple/Noise: <150mV

Power Requirements

Line Power: 100-240 Volts AC, 1.0 Amps, 50/60 Hz

Connections

G 24: (2) leads for ground and +24V

Enclosure

White, 94V-0 polycarbonate

Environmental

Temperature: 32° to 104°F (0° to 40°C) Humidity: 0% to 90% RH (non-condensing)

Dimensions

Height: 2.91 in (74 mm) Width: 1.71 in (44 mm) Depth: 1.39 in (36 mm)

