24-Inch Panel Ready Dishwasher





DDW24G9000AP/DA - Panel Ready



Features & Benefits

- Kitchen Fit Sliding Door hinge system for a seamless design
- Storm Wash+ $^{\scriptscriptstyle \mathsf{TM}}$ with Built-In Water Softener & AutoRelease $^{\scriptscriptstyle \mathsf{TM}}$
- 9 programs + 8 options with downloadable programs
- Adjustable racks and tines for flexible loading (14 pace settings)
- 40 dBa for library-level quiet
- SmartThings Wi-Fi connectivity with AI Energy mode
- · Visual floor light
- Electronic control panel
- · ENERGY STAR Most Efficient
- ADA Certified

Controls	
CONTROL TYPE	Hidden Touch
WI-FI + SMARTTHINGS	Yes
Features	
CAPACITY (PLACE SETTING)	14
TUB MATERIAL	Stainless Steel
NOISE LEVEL (DBA)	40
CUTLERY BASKET	Yes
THIRD RACK	Yes

Dishwasher		
MAXIMUM DOOR PANEL WEIGHT (KG)	4.5 - 12	
SABBATH MODE	Yes	
WATER CONSUMPTION	3.2 gallons/ cycle	
WATER SOFTNER	Yes	
TUB LIGHT	Yes	
FLOOR INFO LIGHT	Yes	
STORM WASH+	Yes	
TOTAL PROGRAMS	9	
PROGRAMS	Normal, Heavy, Auto, Delicate, Preblast, Express 60', Self Clean, Plastic, Download	
TOTAL OPTIONS	8	
OPTIONS	StormWash+, Lower Rack (Half Load), Sanitize, Smart Control, Delayed Start, AI Energy Saving, Auto Open, Sabbath Mode	
AUTORELEASE™ DRYING	Yes	
HEATER	Hidden	
END-OF-CYCLE INDICATOR	Yes	
LEAKAGE SENSOR	Yes	
CANCEL AND DRAIN	Yes	
Weights & Dimensions		
NET WEIGHT (LB)	94.8	
SHIPPING WEIGHT (LB)	103.6	
PRODUCT DIMENSIONS (W x H x D IN INCHES)	23 ¾ x 32 ¼ to 35 ¼ x 22 ¾	
CUTOUT DIMENSIONS (W X H IN INCHES)	35 ¼ x 23 5% to 23 7% x 32 ¼	
Technical Details		
ELECTRICAL REQUIREMENTS	120V, 60 Hz, 15A	
Warranty		
FULL COVERAGE	2 Years	
Accessories (Optional)		
DW-T24PNASR	Panel Kit, Silver Stainless	
DW-T24PNAMS	Panel Kit, Graphite Stainless	

Model numbers, specifications and prices are subject to change at any time without notice. Visit dacor.com for the most up-to-date information. | Effective October 25, 2024

24-Inch Panel Ready Dishwasher

Product Dimensions

A - (IN/MM)	28 ¾ to 29 ⅛ / 730 to 760
B - (IN/MM)	¹¹ % to % / 18 to 22 Recommend ¹³ % / 20
C - (IN/MM)	21 ¾ / 552
D - (IN/MM)	23 ¾ / 595
E - (IN/MM)	32 1/8 / 815
F - (IN/MM)	Total Height 32 ¼ to 33 ¼ / 815 to 860 (Without Sub Foot) 33 ¼ to 35 ¼ / 860 to 895 (With Sub Foot)
G - (IN/MM)	23 3/8 / 594
H - (IN/MM)	2 ½ to 5 ½ / 55 to 130 (Without Sub Foot) 3 ½ to 6 ½ / 100 to 165 (With Sub Foot)
I - (IN/MM)	3 ½ / 90
J - (IN/MM)	Leg Height 0 to 1 ³ / ₄ / 0 to 45 (Without Sub Foot) 1 ³ / ₄ to 3 ½ / 45 to 80 (With Sub Foot)
K - (IN/MM)	2 / 50
L - (IN/MM)	4 % / 125
M - (IN/MM)	23 5% to 23 7% / 600 to 608
N - (IN/MM)	22 5 / 575
0 - (IN/MM)	32 ¼ to 35 ¼ / 820 to 895
P - (IN/MM)	3 1/8 / 100
Q - (IN/MM)	2 / 50





