

Product Specifications

Style Number	VV489
Construction	Solid Polymer Core
Edge Profile	Enhanced Painted Bevel
Nominal Dimensions	7" wide, 48" long
US Units	
Actual Product Width	7.2"
Actual Product Length	48.03"
Wear Layer Thickness	20 mil (0.02")
Overall Product Thickness	0.196"
Core Thickness	0.157"
Attached Underlayment	Attached Cork
Attached Underlayment Thickness	0.039"
Finish	UV Acrylic
Installation Methods	Floating or Direct Glue
Profile	Angle/Tap
Country of Origin	Imported

Packaging

Area per Box	28.84 sq ft
	12 pcs
	48.5 lbs
	50 boxes



2753 Trestle Pine



2753 Trestle Pine



2754 Fortress Pine



2755 Stonewall Pine

Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant







Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

COREtec Pro Plus HD 7"

Warranties


- USF Lifetime
- Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof
- USF 15 Year Heavy Commercial

Coordinating Trim

					
Baby Threshold*	T-Molding*	Quarter Round	Overlap Stairnose*	Flush Stairnose	Overlap Reducer
01V20 94"	02V62 94"	01V46 94"	01V95 94"	02V17 94"	01V70 94"

*Packaged with molding track

Stair Tread


Stair Tread
03Z70 48"