Specifications

Audio Specifications

XLR input Impedance	40kΩ
RCA input Impedance	20kΩ
XLR Output Impedance	40Ω
RCA Output Impedance	20Ω
XLR Max Input Level	9VRMS
XLR Max Output Level	36VRMS
RCA Max Input Level	4.5VRMS
RCA Max Output Level	18VRMS
Frequency Response	20-20kHz ±0.1 250kHz@-3dB
Dynamic Range of XLR Output	129dB@A-weighting, 125dB@Unweighting
Dynamic Range of RCA Output	125dB@A-weighting, 120dB@Unweighting
THD+N of XLR Output	<0.00015%@A-weighting, <0.00020%@Unweighting
THD+N of RCA Output	<0.00040%@A-weighting, <0.00040%@Unweighting
Crosstalk of XLR Output	-140dB
Crosstalk of RCA Output	-130dB
Gain	+12dB
Volume Steps	100

Trigger

Trigger in	DC 6-12V < 10mA
Trigger out	DC 12V/50mA MAX

Power Specs

Power Voltage	AC 100V-120V 50/60Hz or AC 220V-240V 50/60Hz Factory fixed
Standby Power Consumption	< 1W
Maximum Power Consumption	< 70W

Weight & size

Weight	15.7kg (34.6 pounds)
Dimensions	Width: 430 mm (16.93 inches)
	Depth: 349 mm (13.74 inches)
	Height: 106 mm (4.17 inches)

Accessory

RM4C remote control x 1

Power cable x 1

Trigger cable x 1

User manual x 1

Warranty card x 1