Specifications

Turntable

Motor	DC servo motor
Power Supply	DC 3.6 V lithium ion battery
Drive Method	Belt-drive
Speeds	33-1/3 RPM, 45 RPM
Turntable Platter	Aluminum
Wow and Flutter	< 0.25 % (WTD) at 3 kHz
Signal-to-Noise Ratio	> 50dB (DIN-B)
Cartridge Type	VM
Output Level	150 mV nominal at 1 kHz, 5 cm/sec (No phono-output)
Phono Pre-Amp Gain	36 dB nominal, RIAA equalized
Charging Specifications	5 V, 0.5 A
Power Consumption	1.5 W (when charging)
Charging Time	Approx. 12 hours*
Operating Time	Approx. 12 hours*
Input Jack	USB Type-C jack
Dimensions	100 mm (3.9") × 290 mm (11") × 70 mm (2.8") (W×D×H)
Weight	Approx. 900 g (32 oz)
Operating Temperature	5°C to 40°C (41°F to 104°F)
Accessories Included	・USB cable (1.5 m (5'), USB Type-A - USB Type-C) ・RCA audio cable ・45 RPM adapter
Replacement Stylus	ATN3600LC
Communication System	Bluetooth version 5.2
Frequency Band	2.402 GHz to 2.480 GHz
Maximum RF Output	10 mW EIRP
Maximum Communication Range	Line of sight - approx. 10 m (33')
Modulation Method	GFSK, Pi/4DQPSK, 8DPSK
Spread Spectrum Method	FHSS
Compatible Bluetooth Profile	A2DP, AVRCP
Support Codec	SBC
Transmission Band	20 to 20,000 Hz
Notes	* The figures above depend on the operating conditions. For product improvement, the product is subject to modification without notice.