



Color Variants

RC472701
with temperature controlled drawer
Fully integrated appliance

Included accessories

1 x egg box with lid.

Required installation accessories

RA460000
Installation kit for side-by-side
installation (for connecting any two
columns)
RA460010
Additional side heating element

Installation Accessories

RA421710
Stainless steel door panel with handle
RA425110
Long stainless steel door handle
RA460020
Connecting element for vertically split
appliance fronts (for a flush front)
RA460040
Finger protection for extra long
furniture fronts
RA461712
Ventilation grill, stainless steel
RA461713
Ventilation grill, stainless steel

RC472701

Refrigeration column
with temperature controlled drawer
Fully integrated appliance
Width 30" (76.2 cm)

Width 30" (76.2 cm)
Stainless steel interior
Generous LED lighting concept
Solid aluminum door bins
Net volume 17.2 cu.ft.
Temperature controlled drawer (32
°F to 37 °F)
One motorized glass shelf,
adjustable when fully loaded
ENERGY STAR® qualified

Operation

Electronic precision temperature
control with digital temperature display.

Technical features

Dynamic cool air distribution with Multi-
Flow Air system.
Automatic defrosting with defrost water
evaporation.
Activated charcoal air filter.
Energy-saving vacation mode.
Open-door and malfunction warning
system.

Cooling compartment

Net volume 17.2 cu.ft.
(418 liters).
No-frost technology with fast cooling.
Temperature adjustable from 35 °F to
46 °F (+2 °C to +8 °C).
4 safety glass shelves (one is
motorized, two are manually adjustable.
2 fully extendable drawers (low and
high) with transparent front.
Bright interior lighting with LED sidewall
pillars.
3 height adjustable door bins, one of
which is a large gallon door bin.
1 door bin with transparent front flap.

Temperature controlled drawer

Net volume 0.9 cu. ft.
Separate automatic temperature
control with settings for fish (32°F),
meat (35°F) and produce (37°F).
1 continuous, fully-extendable
temperature controlled drawer with
transparent front and integrated
lighting.

Planning notes

Flat hinge.
Door hinge right, reversible.
Door opening angle of 115°, optional
90° door stop.
Max. door panel weight 77 lb.

Consumption data

Energy consumption 0.849 kwh/24 h.
Energy consumption 309.89 kwh/year.
Noise level 39 dB.

Rating

Total rating 0.180 kW.
Total Amps: 10 A.
120 V / 60 Hz
Connecting cable 139 1/3" with plug.

Product Features

Multi-Flow Air Tower
Yes
SUPERCool
Yes
SUPERFREEZE
No
Carbon Air Filter
No
Temperature Controlled Drawer
Yes
Humidity Control Drawer
Yes
Number of Door Bins - Refrigerator
3
Adjustable Door Bins - Refrigerator
No
Tilt-Out Door Bins - Refrigerator
Yes
Gallon Storage Bins
1
Number of Shelves - Refrigerator
4
Door Hinge
Right reversible
Adjustable Shelves - Refrigerator
3
Number of Shelves - Freezer
Reversible Door Hinge
Yes
Adjustable Shelves - Freezer
No

Consumption and connection features

UPC code
825225899921
Color / Material housing
Colour.Material housing
Panel ready
Not possible
Silence level (dBA)
39
Watts (W)
180
Current (A)
10
Volts (V)
120
Frequency (Hz)
60
Total annual energy consumption (kWh)
309.9
Energy Star® qualified
Yes
Approval certificates
ETL, ETL C
Power Cord Length
139 1/3"
Required cutout size (HxWxD) (in)
x 84" x 29 3/4"
Appliance Width (in)
29 3/4"
Height (in)
83 3/4"
Depth (in)
24"
Capacity in 0.75l (bordeaux bottles)
Total unit gross capacity (cu. ft.) - AHAM
17
Product packaging dimensions
(HxWxD) (in)
88.97 x 33.46 x 29.52
Refrigerator Gross capacity (cu. ft.)
17
Freezer Gross capacity (cu ft)
Net weight (lbs)
398
Gross weight (lbs)
433
SKU
RC472701
2017-08-24
Page 1

RC472701
 Refrigeration column
 with temperature controlled drawer
 Fully integrated appliance
 Width 30" (76.2 cm)

2017-08-24
 Page 2

