

36" Series 9 Grill, Charcoal, Natural Gas

Series 9

Stainless Steel | Natural Gas



- This Series 9 Built in 36" Grill is designed for premium outdoor kitchens and will take your outdoor cooking experience to the next level.
- Secondary cooking surface allows you to use a wide repertoire of cooking styles and cater for a crowd
 - Intuitive lighting with bright in-hood lights and bezel lit control dials
 - Easy to lift 90° hood for better access when cooking
 - Delivers 25,000 BTU/hr total power per burner allowing you to precisely control heat from 300°F to 1100°F

DIMENSIONS

Height	27 1/4 "
Width	35 15/16 "
Depth	26 7/8 "

FEATURES & BENEFITS

- Easy Lifting Hood**
- With extra space under the hood for extra large food items, the hood can be smoothly opened, using one hand, to a full 90° for better access and visibility when cooking.
- Storage For Racks And Tools**
- The 6" storage accessory extends your grill to fit a 42" or 54" space. It bolts seamlessly onto either side of the grill to store racks, grates and tools. This accessory is sold separately.

SPECIFICATIONS

Accessories (sold separately)	
6" accessory storage	ASE6-36
Built-in grill cover	ACBI-36E
Griddle plate	BGC-GP
Insulated jacket	BGA36-IJS (optional)
Insulated jacket (with storage accessory unit)	BGA42-IJS (optional)
On cart grill cover	ACC-36E
Optional cart mount	CAD-36E

Burners	
Number of U-burners	3

Cooking Surface Area	
Primary cooking area	630 sq.in.
Secondary cooking area	534 sq.in.
Total cooking area	1164 sq.in.

Features	
Double sided grilling grates	flat and angled position
Full charcoal burner/smoker	•
Full surface searing	•
Grease management system™	•
Hood temperature gauge	•
Ignition system	Hot surface
Metal dials	•
Secondary cooking features	2-level racks and tray

Finish	
Material	304 grade stainless steel
Weather resistant	•

Gas Requirements	
1/2" NPT male	•
Gas type	NG

Operational pressure	4" W.C.
Supply pressure	6" to 9" W.C.

Installation Dimensions

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	34 1/2 "
Insulated jacket for proud cut-out	Varies - check manual

Performance

Total Power	75000 BTU
U-burner power	25000 BTU

Power Requirements

Supply frequency	60 Hz
Supply voltage	120 V

SKU	71647
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

- ↓ Installation Guide Grill EN
- ↓ Guide d'installation FR
- ↓ Guía de instalación SP
- ↓ Service and Warranty
- ↓ User Guide Grill EN
- ↓ Guide d'utilisation FR
- ↓ Guía del usuario SP

A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1.888.936.7872 W www.dcsappliances.com

Other product downloads available at dcsappliances.com