



RADS-121R01 **12,000 BTUH**
Nominal

FEATURES

- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- Energy saver mode, 24-hour on/off timer, dehumidification and auto modes
- Smartphone Compatible



SPECIFICATIONS

Cooling Capacity BTUH	12,000
Approx. Sq. Ft. Cooling	450-550
EER/CEER	3.34/11.4
Heating Capacity BTUH (electric)	N/A
Power Supply	115V 60Hz
Humidity Removal Pts/Hr	2.54
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	320
dB Level (hi/med/low)	61/59/58
Amps Cooling	10.1
Amps Heating	N/A
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Slide-Out Chassis	No
Window Mounting Kit	Yes
Remote Control	Yes
Refrigerant Type	R32
Shipping Weight (lbs.)	75
Dimensions (in.)	Height
	Width
	Depth



RADS-151R01 **15,000 BTUH**
Nominal

FEATURES

- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- Energy saver mode, 24-hour on/off timer, dehumidification and auto modes
- Smartphone Compatible



SPECIFICATIONS

Cooling Capacity BTUH	14,500
Approx. Sq. Ft. Cooling	550-700
EER/CEER	3.3/11.3
Heating Capacity BTUH (electric)	N/A
Power Supply	115V 60Hz
Humidity Removal Pts/Hr	3.17
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	298
dB Level (hi/med/low)	60.5/58/55.5
Amps Cooling	11.8
Amps Heating	N/A
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
Refrigerant Type	R32
Shipping Weight (lbs.)	79
Dimensions (in.)	Height
	Width
	Depth



RADS-183S **18,000 BTUH**
Nominal

FEATURES

- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- Energy saver function, 24-hour on/off timer, dehumidification and auto modes
- **S** = Smartphone Compatible



SPECIFICATIONS

Cooling Capacity BTUH	17,700/18,000
Approx. Sq. Ft. Cooling	700-1000
EER/CEER	11.8/11.8
Heating Capacity BTUH (electric)	N/A
Power Supply	208/230V 60Hz
Humidity Removal Pts/Hr	3.80
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	360
dB Level (hi/med/low)	60/57/54
Amps Cooling	7.5/7.0
Amps Heating	N/A
Maximum Fuse Size	15A
Power Cord	15A Tandem NEMA 6-15P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
Refrigerant Type	R32
Shipping Weight (lbs.)	129
Dimensions (in.)	Height
	Width
	Depth