Specifications

Cartridge & Stylus	
Frequency Response	15 - 30,000 Hz
Channel Separation	30 dB (1 kHz)
Vertical Tracking Angle	19°
Vertical Tracking Force	Refer to “Tracking force information” included in the box.
Recommended Load Impedance	≥ 30 ohms (when head amplifier connected)
Coil Impedance	3.5 ohms (1 kHz)
DC Resistance	3.5 ohms
Coil Inductance	≤ 1 μH (1 kHz)
Output Voltage	0.22 mV (1 kHz, 5 cm/sec.)
Output Channel Balance	0.5 dB (1 kHz)
Stylus Shape	Special line contact stylus
Cantilever	0.26 mm (0.010") diameter solid boron
Static Compliance	20 × 10–6 cm/dyne
Dynamic Compliance	9 × 10–6 cm/dyne (100 Hz)
Dimensions	17.3 mm (0.68") × 17.0 mm (0.67") × 25.5 mm (1.0") (H × W × D)
Accessories Included	・Case (wooden box) ・Non-magnetic screwdriver ・Washer × 2 ・Protector ・Cartridge installation screws (M2.6) (5.0 mm × 2, 8.0 mm × 2, 10.0 mm × 2, 12.0 mm × 2) ・Brush
Threaded Hole	M2.6 × 2
Stylus Curvature Radius	1.5 × 0.28 mil
Type	Direct power system, non-magnetic core coil (MC) type
Weight	11 g (0.39 oz)
Notes	For product improvement, the product is subject to modification without notice.