

Product Specifications

Style Number	VV675	
Construction	Mineral Core	
Edge Profile	Enhanced Painted Bevel	
Nominal Dimensions	9" wide, lengths of 33", 53" and 86"	
	US Units	Metric Units
Actual Product Width	9.06"	23 cm
Actual Product Length	Multiple Lengths	Multiple Lengths
	33.46", 53.14" and	85 cm, 135 cm
	86.61"	and 220 cm
Overall Product Thickness	0.354"	9 mm
Core Thickness	0.315"	8 mm
Attached Underlayment	Attached Cork	
Attached Underlayment	0.039"	1 mm
Thickness		
Finish	PAWdefense™	
Installation Methods	Floating	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	21.79 sq ft	2 sq m
Pieces per Box	18 pcs	
Weight per Box	55.12 lbs	25 kg
Boxes per Pallet	48 boxes	



3015 Suffolk Oak

Colors

				
3015 Suffolk Oak	4016 Ludlow Oak	5017 Savoy Oak	5018 Pronto Oak	5019 Waverly Oak
Color Variation: Moderate	Color Variation: Moderate	Color Variation: Moderate	Color Variation: Slight	Color Variation: Moderate
				
5020 Wythe Oak	6010 Somerset Oak	6011 Heyward Oak	7017 Prescott Oak	8004 Skillman Oak
Color Variation: Moderate	Color Variation: Substantial	Color Variation: Moderate	Color Variation: Slight	Color Variation: Slight

Scratchless 9x86

Performance


Static Load (ASTM F970)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.


Warranties

- 30 Year Scratch
- USF Lifetime
- Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof, Scratch
- 20 Year Light Commercial


Coordinating Trim




Baby Threshold*
 BT6NC | 94"



T-Molding*
 TM6NC | 94"




Quarter Round
 QTRNC | 94"



Flush Stairnose
 FS8NC | 94"

*Packaged with molding track

Stair Tread



Stair Tread
 03Z70 | 48"