

# ARG61PVBIADA456



31.75" x 23.38" x 25" (H x W x D)

Performance series Pharma-Vac 6 cu.ft. ADA height glass door all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

**Highlights:**

- Certified to NSF/ANSI 456 Vaccine Storage Standard
- Sized just under 32" high to fit under lower ADA compliant counters
- Intelligent microprocessor digital temperature controller

**Product Features:**

|                                                    |                                                                                                                                                                                      |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certified to NSF/ANSI 456 Vaccine Storage Standard | Designed and tested to comply with the new NSF Vaccine Storage Standard                                                                                                              |
| Purpose-built design                               | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines                                                                  |
| ADA Compliant                                      | Just under 32" tall designed to fit under ADA compliant counters                                                                                                                     |
| Recessed installation capable                      | Versatile design allows recessed installation under counters or freestanding use                                                                                                     |
| +/-1°C Variation                                   | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Certificate of calibration included                | 2-year calibration certificate included for your records                                                                                                                             |
| Adjustable temperature                             | Intuitive controls let you adjust the interior temperature between +2°C to +8°C                                                                                                      |
| Temperature alarm                                  | Visual and audible alarms alert if the interior temperature rises or falls out of set range                                                                                          |
| Remote alarm contacts                              | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)                     |

## ARG61PVBIADA456 Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 31.75" (81 cm)     |
| Width                      | 23.38" (59 cm)     |
| Width with Door Open       | 23.88" (61 cm)     |
| Depth                      | 25.0" (64 cm)      |
| Depth with Handle          | 26.75" (68 cm)     |
| Depth with door at 90°     | 47.0" (119 cm)     |
| Capacity                   | 6.0 cu.ft. (170 L) |
| Defrost Type               | Automatic          |
| Door                       | Glass              |
| Cabinet                    | White              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Amps                       | 0.75               |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 125.0 lbs. (57 kg) |
| Shipping Weight            | 170.0 lbs. (77 kg) |
| Parts & Labor Warranty     | 2 Years            |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101090634       |
| Refrigerator Features      |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Shelf Type                 | Wire               |
| Shelf Qty                  | 4                  |
| Adjustable Shelves         | Yes                |
| Thermostat Type            | Digital            |
| Fan Type                   | Interior           |
| Refrigerant Type           | R600a              |
| Refrigerant Amount         | 1.66oz.            |
| High Side PSI              | 280.0              |
| Low Side PSI               | 90.0               |
| Interior Light             | Yes                |
| Temperature Range          | 2°C to 8°C         |
| Dimensions                 |                    |
| Interior Height            | 24.5" (62 cm)      |
| Interior Width             | 20.0" (51 cm)      |
| Interior Depth             | 17.0" (43 cm)      |

|                        |               |
|------------------------|---------------|
| Compressor Step Height | 6.5" (17 cm)  |
| Compressor Step Width  | 20.0" (51 cm) |
| Compressor Step Depth  | 5.0" (13 cm)  |

