

Features and Functions

- 460 CFM interior-power ventilator ships standard
- Variable-speed control for custom venting
- Halogen lights for better visibility and efficiency
- Dimmer on lights allows custom lighting separate on/off switch allows consumer to leave dimmer in favorite position
- Heat sensor activates ventilator to full power when cooking temperatures reach uncomfortable levels
- Recirculating kit with air-purifying charcoal filters available and sold separately if exterior ducting is not desirable
- Adjustable duct cover comes standard with product

Easy Cleanup

- Mesh filters made entirely of stainless steel for durability and long life; efficiently remove grease and heated vapors from the air
- Dishwasher-safe filters are easily removed for quick cleaning
- Design of low-profile filter system means less interior hood space to be cleaned
- Interior of rangehood canopy has stainless steel liner for increased rigidity, seamless appearance, and easy cleaning

Installation Accessories

- Recirculating kit for 30"W. Hood (DRK30)
- Recirculating kit for 36"W. Hood (DRK36)

Finishes

• Available in Stainless Steel (SS), Black (BK), and White (WH)



- One-year full complete product
- Ninety-day full cosmetic parts such as glass, painted items, and decorative items
- Five-year limited all ventilator motors



Wall Hood with Standard Ventilator 30" and 36" Widths

CHIMNEY WALL HOODS WITH STANDARD VENTILATOR RVCH330 – 30" WIDE / RVCH336 – 36" WIDE



DESCRIPTION	CHIMNEY WALL HOODS WITH STANDARD VENTILATOR									
	DUCT COVERS			NUMBER OF	NUMBER OF	RECOMMENDED DUCT SIZE		MAXIMUM AMPS		
	WIDTH	DEPTH	HEIGHT	LIGHTS	FILTERS	INTERIOR	EXTERIOR	INTERIOR	IN-LINE	EXTERIOR
CHIMNEY HOODS WITH STANDARD INTERIOR-POWER VENTILATOR – 24" DEEP A 460 CFM BLOWER IS SHIPPED WITH HOOD										
30" W. RVCH330	16″	12″	18"- 30"	2	2	7″	-	5.6	5.6	N/A
36" W. RVCH336	16″	12″	18"- 30"	2	2	7″	-	5.6	5.6	N/A





VIKING RANGE, LLC 111 FRONT STREET GREENWOOD, MISSISSIPPI 38930 USA For detailed product information, model numbers, or to request a quote call 1-888-845-4641 or visit vikingrange.com © 2013 Viking Range, LLC I Specifications subject to change without notice.