

LUXURY VINYL

HEARTLANDS
fiberglass sheet



707 Dakota

shawfloors.com

Shaw
FLOORS

For reference purposes only if printed or downloaded.

	US Units	Metric Units
Style Number	0529V	
Construction	Residential Resilient - Sheet	
Profile	Direct Glue	
Overall Thickness	0.055"	1.399 mm
Wear Layer Thickness	10 mil (0.01")	0.3 mm
Finish	Opticlean Urethane	
Installation	Glue	
Installation Grade	Above, On, Below	
FloorScore Certified	Yes	
Residential Warranty	5 Years DuraTru Residential Limited Warranty	
Smoke Density (ASTM E662, Flaming Mode)	Passes, <450	
Radiant Panel (ASTM E648)	Passes, Class I	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Features

This is an economical product that is durable and easy to clean. Realistic designs to capture the essence of hardwoods pulled straight from the country. Traditional warm greys and toned browns that give the feeling of home-colors that stand the test of time and weather.

Colors



109 Springfield

Pattern: 39.4" W x 39.4" L
Drop: 13.13"



202 Madison

Pattern: 39.37" W x 39.37" L
Drop: 19.7"



510 Iowa

Pattern: 39.4" W x 59.1" L
Drop: 26.27"




511 Lincoln

Pattern: 39.37" W x 39.37" L
Drop: 19.7"



550 Peoria

Pattern: 39.4" W x 39.4" L



707 Dakota

Pattern: 39.4" W x 59.1" L
Drop: 19.7"

Suggested Adhesive

Style Name	Style Number
SHAW 350 PS ADH 4G	VS024
124VS	SHAW 350 PS ADH 1G
053VS	153VS
VS186	100SA
SHAW SV-1200 4 GAL	VS187



MADE IN THE USA

