

COMMERCIAL THROUGH RETAIL

COIN DROP STACKED DRYERS AND STACKED WASHER-DRYERS



| Product | Stacked Dryer | |
|---------------------------------------|--------------------------------------|--------------------------------------|
| | Tall | Short |
| Color | White | |
| Capacity - lb (kg) | 18 (8.2) ea | |
| Cylinder Volume - cu.ft. (liters) | 7.0 (198) ea | |
| Motor (Thermal Protected) - HP | 0.33 | |
| Type of Gas (Gas Models Only) | Factory Equipped Natural | |
| Available Cycles | High, Medium, Low, Delicate, No Heat | |
| Air Outlet Diameter - in | 4 | |
| Exhaust Airflow - cfm (liters/sec) | 220 (105) | |
| Electrical Requirements (v/Hz/Ph-Amp) | *Electric | 208-240/60/1-30 Amp |
| | Gas | 120/60/1-15 Amp |
| Heating Element | Electric | 5350W, 240V / 4750W, 208V |
| | Gas | 25,000 Btu |
| Net Weight - lb (kg) | 270 (122) | |
| Shipping Weight - lb (kg) | 280 (127) | |
| Shipping Dimensions Approx. - in | Width | 33 |
| | Depth | 30 |
| | Height | 80 |
| Agency Approvals | Electric | cULus |
| | Gas | cCSAus |
| Model No. | SSENCAGS176TW01 SSGNCAGS116TW01 | SSENCFS176TW01 SSGNCFS116TW01 |
| Required Coin Kits (sold separately) | Coin Box Model #: CK043 (2 required) | Coin Box Model #: CK042 (2 required) |

Note (not supplied): Each stacked dryer pocket requires its own power cord and the stacked washer-dryer requires two power cords, one for washer, one for dryer.

For Commercial Use Only

| Product | Stacked Washer-Dryer | |
|--|--------------------------------------|--------------------------------------|
| | Washer | Dryer |
| Color | White | |
| Capacity - lb (kg) | 21.5 (9.5) | 18 (8.2) |
| Cylinder Volume - cu.ft. (liters) | 3.42 (96.8) | 7.0 (198) |
| Spin Speed G-Force (RPM) | 440 (1200) | — |
| Motor Size - HP | 0.9 | 0.33 |
| Type of Gas (Gas Models Only) | — | Factory Equipped Natural |
| Water Consumption Per Cycle - g (liter)** | 13.68 (51.8) | — |
| IWF (Water Factor) - gal/ft ³ (liters/liter/cycle)** | 4.0 (0.53) | — |
| MEF ₇₂ (Modified Energy Factor) ft ³ /kWh/cycle (Liters/kWh/cycle)** | 2.20 (62.3) | — |
| Available Cycles | Normal, Synthetic, Delicate | High, Medium, Low, Delicate, No Heat |
| Air Outlet Diameter - in | — | 4 |
| Exhaust Airflow - cfm (liters/sec) | — | 220 (105) |
| Electrical Requirements (v/Hz/Ph-Amp) | *Electric | 120/60/1-15 Amp |
| | Gas | 208-240/60/1-30 Amp |
| Heating Element | Electric | 5350W, 240V 4750W, 208V |
| | Gas | 25,000 Btu |
| Net Weight - lb (kg) | 385 (175) | |
| Shipping Weight - lb (kg) | 417 (189) | |
| Shipping Dimensions Approx. - in | Width | 34 |
| | Depth | 30 |
| | Height | 80 |
| Agency Approvals | Electric | cULus |
| | Gas | cCSAus |
| Model No. | STENCFS176TW01, STGNCFS116TW01 | |
| Required Coin Kits (sold separately) | Coin Box Model #: CK042 (2 required) | |

| Dimensions | Width - in | Height - in | Depth - in | Floor to Door Opening - in | Door Swing - in |
|------------------------------|------------|-------------|------------|----------------------------|-----------------|
| Stacked Dryer - Tall | 26.875 | 78.17 | 28 | 15.44 | 23.5 |
| Stacked Dryer - Short | 26.875 | 76.5 | 28 | 15.44 | 23.5 |
| Stacked Washer-Dryer - Short | 26.875 | 76.5 | 27.73 | 14.5*** | 23.5 |

* Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.

** Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

*** For ADA compliance turn legs out from base 0.5 inches

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For additional accessories and warranty, please refer to the price list.