

H 6880-2 BP

30 Inch Convection Oven

- The multi-talented Miele for the highest demands.



- Multicolored TFT touch display with clear text - M Touch
- Perfect baking and roasting results -Moisture plus
- Precise cooking temperature – Wireless Precision Probe
- Perfect results with ease -MasterChef Programs
- Plenty of room and versatility

EAN: 4002516000358 / material number: 10752160

EAN: 4002516000358 / material number: 10752160	
Construction type	
Built-in wall oven	•
Design	
PureLine	<u> </u>
Appliance color	Clean Touch Steel
Control panel	M Touch
Convenience features	
Precise temperature control	75 – 575 °F
Wireless Precision Probe	<u> </u>
Wireless roast probe	<u> </u>
Crisp Function	•
Operating modes	
Defrost	<u> </u>
MasterChef automatic programs	More than 100
Auto roast	<u> </u>
Gentle bake	•
Broil	•
Broil	•
Convection Bake	•
Intensive bake	•
Moisture plus	•
Slow roast	•
Surround	•
Browning	•
Bake	•
Convection Broil	•
Special modes	•
Control panel	
MultiLingua	•
Search function automatic programs	•
Timed bursts of steam	•
Polyphonic acoustic signals	•
Time of day display	•
Polyphonic acoustic signals	•
Date display	•
Minute minder	•
Time buffer in h	200
Start-stop programming	•
Automatic switch-off	•
Programmable cooking time	•
Entry via number keypad	
Actual temperature display	•
Default temperatures	
Acoustic signal when desired temperature is reached	•
Sabbath program	<u> </u>
Individual settings	
Door	
CleanGlass door	•
Door contact switch	•
Door hinge side	Bottom
Door tillinge side	DOLLOITI

More information at www.MieleUSA.com



H 6880-2 BP

30 Inch Convection Oven

- The multi-talented Miele for the highest demands.



Cavity	
Cavity volume in cu.ft(l)	4.59 (130)
No. of rack levels	6
Labeling of rack levels	•
No. of halogen lamps	double
TwinPower hot air fans	•
Cleaning convenience	
Stainless steel front with Clean Touch Steel surface	•
Self-cleaning	•
AirClean catalyzer	_ •
Foldable broil heater element	•
Efficiency and sustainability	
Energy-saving lighting circuit	•
Residual heat utilization	_ •
Rapid PreHeat	•
Safety	
Appliance cooling system with cool touch front	•
Safety cut-out	•
System lock	•
Door contact switch	•
Door lock during self cleaning	•
Technical data	
Niche depth in in. (mm)	24 1/8 (610)
Appliance width in in.(mm)	28 3/8 (720)
Appliance height in in.(mm)	28 (711)
Weight in lbs. (kg)	184.53 (83.7)
Voltage in V	240/208
Fuse rating in A	30
Number of phases	1
Standard accessories	
Universal baking tray with PerfectClean	_ 1
Self Clean ready baking and roasting rack	_ 3
Connection wire with plug	•