DCM-390/290

DENON

High Performance CD Auto Changer with HDCD*, MP3 and WMA (Windows Media[®] Audio) Decoders.

The DCM-390/290, a 5-disc carousel CD changers equipped with HDCD*, MP3 and WMA decoders, let you not only enjoy regular audio CDs, but also HDCD* discs, MP3 and WMA encoded CD-R/RW discs.



CD-R/RW Playback

MP3 and WMA Decoders

The DCM-390/290 play finalized CD-R/RW discs containing MP3 or WMA audio files. When they are in MP3 or WMA format, a single CD-R/RW disc can contain up to 10 times more tracks than an ordinary audio CD. CD-R/RW discs containing a large number of MP3/WMA files are ideal for use in long-play applications such as background music.

■ HDCD Decoding (DCM-390 only)

Advanced Multilevel Noise Shaping DAC

The DCM-390/290 features a Multilevel Noise Shaping DAC. This multi-level modulation powerfully removes the adverse effects of jitter, and because it is built into the output amp, a clean analog output with suppressed high-frequency interference can be directly obtained.

8-Times Oversampling Digital Filter

Increasing the oversampling frequency by a factor of eight makes possible an extraordinary degree of attenuation and reduces frequency irregularities in the audio range to an absolute minimum.

Remote Control IN/OUT

When the DCM-390/290 is cable connected to an amplifier or receiver that supports the Remote Control IN/OUT feature, you can operate the DCM-390/290 via the remote sensor on the amplifier or receiver. This feature is very handy when the DCM-390/290 is placed in another room.

Full Selection of Program Playback

The DCM-390/290 lets you combine up to 32 tracks from the five or fewer CDs which are loaded.

3-Mode Random Playback

Full Random/Program Random/Disc Sequential Random

Intelligent Disc Scan

The Disc Skip button can rotate the carousel tray clockwise or counterclockwise when searching for a disc. (Counter-clockwise rotation is operable only by remote controller.)


20-Selection Music Calendar Display

- Optical/Coaxial Digital Outputs
- Headphone Jack

S

RS-232C terminal (DCM-390 only)

Specifications		
Audio Section	DCM-290	DCM-390
Frequency response	2 Hz - 20 kHz	2 Hz - 20 kHz
Dynamic range	98 dB	100 dB
Signal-to-noise ratio	108 dB	112 dB
Total harmonic distortion	0.003%	0.0027%
Channel separation	98 dB	98 dB
Line out level (Fix)	2.0 V rms	2.0 V rms
Digital Output	Optical/Coaxial	Optical/Coaxial
General		
Power supply	AC 120 V, 60 Hz	AC 120 V, 60 Hz
Power consumption	15 W	15 W
Dimensions	17.1(W) x 4.7(H) x 15.8(D) inch 434(W) x 120(H) x 400(D) mm	17.1(W) x 4.7(H) x 15.8 (D) inch 434(W) x 120(H) x 400(D) mm
Weight	10.0 lbs. 0.0 lvs.	10.0 lbs. 0.0 lvs.
110igint	13.9 lbs, 6.3 kg	13.9 lbs, 6.3 kg





Denon Brand Company D&M Building, 2-1 Nisshin-cho, Kawasaki-ku, Kawasaki-shi, Kanagawa, 210-8569 Japan w.denon.com

Denon Electronics (USA), LLC. 100 Corporate Drive, Mahwah, New Jersey 07430 USA TEL: 201-762-6500 usa.denon.com

Denon Canada Inc 505 Apple Creek Blvd, Unit 5, Markham, Ontario, Canada L3R 5B1 TEL: 905-475-4085 ca.denon.com