



PRODUCT DATA SHEET  
**CLASSIC I/2**

**SPENDOR**

MADE FOR MUSIC. DESIGNED FOR YOU.

With a meticulously refined crossover network, enhanced cabinet structure and elastomer panel damping the Classic 1/2 delivers music with captivating coherence and transparency. Spondor Classic 1/2 continues to offer the ultimate in pure listening pleasure for serious enthusiasts.

## HIGHLIGHTS

- The Classic 1/2 is built around two totally new Spondor drive units. The 22cm bass driver features an advanced polyamide fibre reinforced polymer cone with a Kevlar stabiliser dome. The 15cm midrange uses EP77 polymer cone material for ultra-low colouration.
- The new 1/2 delivers a truly captivating sound with unprecedented transparency and dynamic contrast and legendary vocal performance that the Spondor brand is known for.
- Available in two luxurious real wood veneer finishes – walnut and cherry.
- Use on the dedicated Spondor Classic 1/2 Stand for best results.
- Designed and Manufactured in the UK.

## TECHNICAL SPECIFICATION

Description	3-way stand mount loudspeaker
Enclosure type	Twin port reflex loaded
Input connection	Three pairs gold plated precision binding posts
Typical in-room response	30Hz – 25kHz
Power handling	150 watts unclipped programme
Amplifier	25-200 watts
Sensitivity	87dB for 1 watt at 1 metre
Nominal impedance	8 ohms (min 4.0)
HF driver	2.2cm polyamide dome
MF driver	15cm EP77 polymer cone
LF driver	22cm polyamide & polymer cone with Kevlar® composite stabilizer
Crossover frequency	415Hz, 2.7kHz
Net Weight	22.6kg
Height	62.1cm
Width	30.8cm
Depth	37.4cm
Finishes	Cherry, Walnut
Included	Magnetic grille
Recommended stand	Dedicated Spondor Classic 1/2 Stand (not supplied)



Cherry



Walnut

**SPENDOR**

Spondor Audio Systems Ltd, G5 Ropemaker Park, South Road, Hailsham, East Sussex BN27 3GY UK  
+44 (0)1323 843474    [info@spondoraudio.com](mailto:info@spondoraudio.com)    [spondoraudio.com](http://spondoraudio.com)