



Special Notes: LED lights. This model is not available with heat lamps. Shown with optional duct cover (sold separately). Optional duct covers are available in standard and custom sizes. Galley rail included.


WIDTH:	60"			
DEPTH:	21"			
HEIGHT:	9"			
CFM:	900			
SONES:	6.3			
AMPS:	6.0			
# LIGHTS:	4			



## **CONNECTION DIAGRAM**



## **REC. MOUNTING HEIGHT\***



\* Exceeding recommended mounting height may compromise performance.

## **ELECTRICAL/MECHANICAL SPECIFICATIONS FOR BLOWER UNIT**

VP562 transition centers outlet over top of hood.

MODEL	VOLTS	AMPS+	HZ	RPM	CFM SP@0.0"	EQUIV CFM\$	CFM SP@0.1"	CFM SP@0.2"	CFM SP@0.3"	MIN. ROUND DUCT SIZE	SONES#
B200 Dual & B100 Single	115	6.0	60	1550	900	1350	804	725	655	10" (79 sq. in.)	6.3

<sup>+</sup> This model is equipped with LED lighting: (2 lights: 30" - 41", 3 lights: 42" - 53", 4 lights: 54" - 66").

(B200 Dual Blower & B100 Single Blower)

<sup>#</sup> Ratings in accordance with the Standard Test Code by the Energy Systems Laboratory of the Texas Engineering Experiment Station.



<sup>\$</sup> Because the Magic Lung blower uses centrifugal filtration rather than conventional baffle or mesh filters, the Magic Lung blower can handle cooking equipment with higher cubic feet per minute (CFM) requirements and can deliver equivalent CFM much more efficiently than other filtration systems. When comparing the Magic Lung with other blower units made by other manufacturers, use the "Equivalent CFM".