





600 CFM/14.0 Sones @ 0.10" SP.

Dimensions

Overall bottom projection - 193/4" Available widths: 357/8"

Hood Body

Brushed 430 stainless steel

Motor

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz.

Lighting

Two - GU10 base, MR16, 50 watt halogen lights.

Ducting Options

Vertical ducting: 6" round duct adapter complete with back draft damper ensuring quiet operation.

Ductless: Requiers charcoal filter (not included).

Blower Wheel

Dual inlet, electronically balanced polymetric centrifugal blower wheel, 53/4" width 59 paddles.

Mounting

Wall mounted with included mounting bracket. Install 24" to 30" from cooking surface.

Filters


Grease Filter: BCGF-01 (included). Charcoal Filter: BCCF-01 (not included).

Available Finishes

Stainless Steel.







EXPANDED PERFORMAN								CE			
ı		Static Pressure (inches of w.g.)					Sones	Fan Speed	Power		
ı		0	0.1	0.25	0.5	0.75	1.0	@ .1 SP	RPM	Watts	Amps
ı	Air Flow - CFM	603	600	594	578	557	531	14.0	2560	551.0	3.8

PROJECT							ARCHITECT			
LOCATIO	LOCATION						ENGINEER			
CONTRACTOR							SUBMITT	ED BY	DATE	
FAN Number	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048

Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767

Fax: (905) 456-1015

Canada: 8 Edvac Drive

Updated 2-13 Specifications subject to change without notice.