



LUMIX GX8 4K Mirrorless Interchangeable Lens Camera Body Only – Black DMC-GX8KBODY

- **MORE DETAILS**

- **Imaging**
- **Lens Mount Micro Four Thirds**
- **Camera Format Micro Four Thirds (2x Crop Factor)**
- **Pixels Actual: 21.77 Megapixel**
- **Effective: 20.3 Megapixel**
- **Max Resolution 5184 x 3888**
- **Aspect Ratio 1:1, 3:2, 4:3, 16:9**
- **Sensor Type / Size MOS, 17.3 x 13 mm**
- **File Formats Still Images: JPEG, MPO, RAW**
- **Movies: AVCHD Ver. 2.0, MP4**
- **Audio: AAC, Dolby Digital 2ch**
- **Dust Reduction System Yes**
- **Memory Card Type SD**
- **SDHC**
- **SDXC**
- **Image Stabilization Sensor-Shift**
- **AV Recording**
- **Video Recording Yes, NTSC**
- **Video Format 4K**
- **MP4**
- **3840 x 2160p / 30 fps (100 Mbps)**
- **3840 x 2160p / 24 fps (100 Mbps)**
- **High Definition**

- **MP4**
- **1920 x 1080p / 60 fps (28 Mbps)**
- **1920 x 1080p / 30 fps (20 Mbps)**
- **High Definition**
- **MP4**
- **1280 x 720p / 30 fps (10 Mbps)**
- **Standard Definition**
- **MP4**
- **640 x 480p / 30 fps (4 Mbps)**
- **High Definition**
- **AVCHD**
- **1920 x 1080p / 60 fps (28 Mbps)**
- **1920 x 1080p / 30 fps (24 Mbps)**
- **1920 x 1080p / 24 fps (24 Mbps)**
- **High Definition**
- **AVCHD**
- **1920 x 1080i / 60 fps (17 Mbps)**
- **Aspect Ratio 4:3, 16:9**
- **Video Clip Length Up to 29 Min 59 Sec**
- **Audio Recording Built-in Mic: With Video, Stereo**
- **Optional External Mic: With Video, Stereo + Mono**
- **Focus Control**
- **Focus Type Auto & Manual**
- **Focus Mode Continuous-servo AF (C), Flexible (AFF), Manual Focus (M), Single-servo AF (S)**
- **Autofocus Points Contrast Detection: 49**
- **Viewfinder/Display**
- **Viewfinder Type Electronic**
- **Viewfinder Pixel Count 2360000**
- **Viewfinder Eye Point 21.00 mm**
- **Viewfinder Coverage 1**
- **Viewfinder Magnification Approx. 0.77x**
- **Diopter Adjustment - 4 to +3 m**
- **Display Screen 3" Rear Touchscreen Swivel Touchscreen OLED (1,040,000)**
- **Screen Coverage 1**
- **Exposure Control**

- ISO Sensitivity Auto, 200-25600 (Extended Mode: 100-25600)
- Shutter Type: Electronic & Mechanical
- Speed: 60 - 1/8000 second
- Type: Electronic & Mechanical
- Speed: 30 - 0 minute in Bulb Mode
- 1/25 - 1/16000 second in Movie Mode
- Type: Electronic
- Speed: 1 - 1/16000 second
- Remote Control DMW-RSL1 (Optional)
- Metering Method Center-weighted average metering, Multiple, Spot metering
- Exposure Modes Modes: Aperture Priority, Manual, Programmed Auto, Shutter Priority
- Metering Range: EV 0.0 - EV 18.0
- Compensation: -5 EV to +5 EV (in 1/3 EV steps)
- White Balance Modes Auto, Cloudy, Color Temperature, Daylight, Flash, Incandescent, Shade, White Set White Set 2, White Set 3, White Set 4
- Burst Rate Up to 10 fps at 20.3 MP for up to 100 frames
- Up to 8 fps at 20.3 MP for up to 100 frames
- Up to 6 fps at 20.3 MP for up to 100 frames
- Up to 5.5 fps at 20.3 MP for up to 100 frames
- Up to 30 fps at 8 MP
- Flash
- Flash Modes Auto
- Auto/Red-eye Reduction
- Forced On
- Forced On/Red-eye Reduction
- Off
- Slow Sync
- Slow Sync/Red-eye Reduction
- Built-in Flash No
- Max Sync Speed 1 / 250 seconds
- Flash Compensation -3 EV to +3 EV (in 1/3 EV steps)
- Dedicated Flash System TTL
- External Flash Connection Hot Shoe
- Performance
- Continuous Shooting Up to 30 fps
- Self Timer 10 seconds, 2 seconds

- **Interval Recording** Yes
 - **Connectivity** 2.5mm Sub-mini (2-Ring), HDMI D (Micro), USB 2.0, Viera Link
 - **Wi-Fi Capable** Yes
 - **Software System Requirements** Windows: Vista, 7, 8, 8.1
 - **Mac:** OS X 10.5 or later
 - **Power**
 - **Battery** 1x DMW-BLC12 Rechargeable Lithium-ion Battery Pack, 7.2 VDC, 1200 mAh
 - **AC Power Adapter** DMW-AC10 with DMW-DCC8 (Optional)
 - **Operating/Storage Temperature** Operating
 - **32 to 104°F (0 to 40°C)**
 - **Humidity:** 10 - 80%
 - **Physical**
 - **Dimensions (WxHxD)** 5.2 x 3.1 x 2.5" / 133.2 x 77.9 x 63.1 mm
 - **Weight** 1.07 lb / 487 g with battery and memory card
-

- ◦ **UPC885170254534**
-