



DS Series 6x8" Coax

The DS 6x8-Inch Coaxial Speakers are the upgrade you need for great sound in your doors.

A ribbed, UV-treated foam surround and rigid polypropylene cone with EVC™ (Extended Voice Coil) technology give you the best sonic quality and the deepest bass in a full range speaker.

These DS speakers work best with 50 watts of recommended power. See below for more details.

Specifications

Model	
DSC680	
Speaker Design	
2 - Way	
Woofer [in, mm]	
6x8, 160x200	
Mid [in, mm]	
n/a	•

11/2020 201
Tweeter [in, mm]
1/2, 13
B
Rated Impedance [Ω]
4
Peak Power (watts, per ANSI/CTA-2031-A)
200
Recommended Amplifier Power (watts RMS)
50
Sensitivity [1W, 1m]
90
For any and Boron and Albert
Frequency Response [Hz] 45-20k
45-20K
Mounting Hole Diameter [in, mm]
5x7 3/16, 126x182
Ton Mount Douth (in mm)
Top Mount Depth [in, mm] 3/8, 9
310, 9
Bottom Mount Depth [in, mm]
2-3/16, 56
Tweeter Protrusion [in, mm]
0
Grilles
No
Tweeter Magnet Material
Neodymium
Tweeter Dome Material
PEI (polyether imide)
Tweeter Design
Balanced dome
Woofer Cone Material
Polypropylene
i diypi dpyrene
Woofer Surround Material
Polyester foam

Support

Manuals