



810 WEST WASHINGTON BOULEVARD
CHICAGO, IL 60607

8566 KRUM AVENUE
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM
+1.800.868.1699

K750HS Hybrid Fire Freestanding Grill



PRODUCT FEATURES


- 33" x 22" (726 square inches) of primary grilling surface
- Three cast bronze Dragon Burners™, 26,500 BTUs each (LP)
- Natural gas, bulk liquid propane, or 30 lb liquid propane cylinder
- Barbecue burner for indirect, low-temperature cooking
- Rotisserie system with infrared burner; motor mounted in cabinet; flip-up warming rack
- Dual cooktop burners, 20,500 BTUs each (LP)
- Safety valves for every burner and electronic control bezels with flame sensor LED indicators
- Kalamazoo's Advanced Cooking Concept with deep hopper cleaning
- Single Hybrid Fire Grilling System Drawer
- Right end cabinet for optional propane cylinder storage
- Optional laser-cut grilling surfaces with your choice of patterns optimized for cooking meat, fish, and vegetables
- Marine-grade stainless steel available

Overall Width / Installation Width	82.25 in (2090 mm)
Overall Depth / Installation Depth	32 in (814 mm)
Overall Height / Counter Height	54.63 in (1388 mm) / 36 in (915 mm) +/- 1 ¼ in (33 cm)
Approximate Product Weight	630 lb (286 kg)
Gas Requirements	Natural Gas: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 7 i.w.c. at grill location. See BTU information below for pipe sizing. Bulk Propane: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick disconnect provided. Gas service line to deliver 11 i.w.c. at grill location. See BTU information below for pipe sizing. Propane Cylinder: 30 lb (13.6 kg) cylinder. 2 ft. (61 cm) gas hose with dual regulator provided.
Electrical Requirements	120VAC/60Hz Includes 1 ft. (30.5 cm) 3-prong grounded power cord. 1.5V "AAA" battery x 1 for cooktop burner ignition.
Maximum AMP usage	3 amps
Main Burners Rating	79,500 BTU liquid propane / 72,000 BTU natural gas
Total BTUs	140,750 BTU liquid propane / 130,500 BTU natural gas

Ensure proper gas pipe sizing. Diameter and length of the supply pipe may limit the pressure and BTU delivery.

For outdoor use only. Do not build the grill into a combustible enclosure. Maintain at least 6 inches (153 mm) of clearance between the sides and back of the grill and any combustible surface. Never place the grill underneath an overhead combustible structure or surface. Do not place the grill in a location where the rear hood openings are likely to be exposed to a strong wind.

High altitude kit available.



Do not place the grill in a location where the rear hood openings are likely to be exposed to strong wind. A wind break wall is recommended for installations where the prevailing wind may be a problem.

WARNING: This product can expose you to chemicals including nickel, which are known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warningsca.gov



810 WEST WASHINGTON BOULEVARD
CHICAGO, IL 60607

8566 KRUM AVENUE
GALESBURG, MI 49053

KALAMAZOOGOURMET.COM
+1.800.868.1699

K750HS Hybrid Fire Freestanding Grill

