

# ARG3PV456



34" x 18.5" x 19" (H x W x D)

Performance series Pharma-Vac 3 cu.ft. counter height glass door all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

## Highlights:

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

## Product Features:

Certified to NSF/ANSI 456 Vaccine Storage Standard Certified to NSF/ANSI 456 Vaccine Storage Standard

|                                                 |                                                                                                                                                                                      |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Purpose-built design                            | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines                                                                  |
| +/-1°C Variation                                | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Certificate of calibration included             | 2-year calibration certificate included for your records                                                                                                                             |
| Antimicrobial silver ion-coated handle          | Powder-coated handle with naturally occurring silver ions to help reduce germ spread                                                                                                 |
| Adjustable temperature                          | Intuitive controls let you adjust the interior temperature between +2 to +8°C                                                                                                        |
| Temperature alarm                               | Visual and audible alarms alert if the interior temperature rises or falls out of set range                                                                                          |
| Remote alarm contacts                           | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)                     |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup                                                                                         |

## ARG3PV456 Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Height of Cabinet          | 34.0" (86 cm)      |
| Width                      | 18.5" (47 cm)      |
| Width with Door Open       | 19.0" (48 cm)      |
| Depth                      | 19.0" (48 cm)      |
| Depth with Handle          | 20.75" (53 cm)     |
| Depth with door at 90°     | 36.0" (91 cm)      |
| Capacity                   | 3.0 cu.ft. (85 L)  |
| Defrost Type               | Automatic          |
| Door                       | Glass              |
| Cabinet                    | White              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S to NSF 456   |
| Amps                       | 0.6                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 87.0 lbs. (39 kg)  |
| Shipping Weight            | 123.0 lbs. (56 kg) |
| Parts & Labor Warranty     | 2 Years            |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101090627       |
| Refrigerator Features      |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Shelf Type                 | Wire               |
| Shelf Qty                  | 4                  |
| Adjustable Shelves         | Yes                |
| Thermostat Type            | Digital            |
| Fan Type                   | Interior           |
| Refrigerant Type           | R600a              |
| Refrigerant Amount         | 1.06oz.            |
| Interior Light             | Yes                |
| Temperature Range          | 2 to 8°C           |
| Sound Level                | 37.6 dB            |
| Dimensions                 |                    |
| Interior Height            | 28.38" (72 cm)     |
| Interior Width             | 15.25" (39 cm)     |
| Interior Depth             | 11.75" (30 cm)     |

|                        |                |
|------------------------|----------------|
| Compressor Step Height | 8.0" (20 cm)   |
| Compressor Step Width  | 15.25" (39 cm) |
| Compressor Step Depth  | 3.75" (10 cm)  |

