

ACR22GLHD



23.13" x 18.88" x 21" (H x W x D)

Compact healthcare all-refrigerator with self-closing glass door, front lock, digital controls, and external temperature readout.

Highlights:

Designed and constructed for reliable cold storage in healthcare facilities

External temperature readout of the current and high/low temperatures

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Product Features:

EQTemp Healthcare Refrigerator	All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities	
Temperature Range: 2º to 8ºC	Preset to 5°C as recommended for many storage applications	
Compact size	Full 1.94 cu.ft. capacity inside conveniently slim footprint	
External temperature readout	Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
Buffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines	
Access port	3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of user- provided monitoring equipment	
Factory installed lock	Keyed lock for a secure interior (2 keys included)	
Automatic defrost	Reduced user maintenance with automatic defrost	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com





ACR22GLHD Specifications:

Height of Cabinet 23.13" (59 c Width 18.88" (48 c Width with Door Open 19.13" (49 c Depth 21.0" (53 c Depth with door at 90° 38.38" (97 c Capacity 1.94 cu.ft. (55	<i>,</i>	
Width with Door Open 19.13" (49 c Depth 21.0" (53 c Depth with door at 90° 38.38" (97 c	m)	
Depth 21.0" (53 c Depth with door at 90° 38.38" (97 c		
Depth with door at 90° 38.38" (97 c	m)	
· · ·	m)	
Capacity 1.94 cu.ft. (55	m)	
	L)	
Defrost Type Automa	tic	
Door Gla	ss	
Cabinet Wh	ite	
US Electrical Safety E	TL	
Canadian Electrical ETL Safety	-C	
Amps ().9	
Voltage/Frequency 115 V AC/60	Ηz	
Weight 52.9 lbs. (24 k	(g)	
Shipping Weight 78.0 lbs. (35 k	(g)	
Parts & Labor Warranty 1 Ye	ar	
Compressor Warranty 5 Yea	ars	
UPC 7611011076	08	
Refrigerator Features		
Door Swing Lt	HD	
Reversible Factory Reversil	ole	
Shelf Type W	ire	
Shelf Qty	1	
Thermostat Type Digi	tal	
Dig	ior	
Fan Type Inter		
	0a	
Fan Type Inter		
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850		
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.	DZ.	
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.	oz. 45	
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.Low Side PSI0.Level Legs Qty0.	oz. 45 85	
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.Low Side PSI0.Level Legs Qty	oz. 45 85 2 ′es	
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.Low Side PSI0.Level Legs QtyInterior LightYY	oz. 45 85 2 ′es	
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.Low Side PSI0.Level Legs Qty0.Interior LightYTemperature Range2° to 8	0z. 45 85 2 ′es ⁰C	
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.Low Side PSI0.Level Legs Qty0.Interior LightYTemperature Range2º to 8Dimensions0.	0z. 45 85 2 ∕es ∘C m)	
Fan TypeInterRefrigerant TypeR60Refrigerant Amount0.850High Side PSI1.Low Side PSI0.Level Legs Qty0.Interior LightYTemperature Range2º to 8Dimensions16.25" (41 c	0z. 45 85 2 ∕es °C m)	

Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	5.5" (14 cm)



Front

