


- The Captur[™] system's advanced blower design features a forward positioned centric inlet to remove smoke and odor faster. Three-speed blower control exhausts at a strong 400 CFM.
- · Forward placement and smooth-flow blower wheel design ensure quiet, < 0.5 sone operation at normal speed.
- · Bright, three-level LED modulessupported by a 3-year warranty illuminate evenly and are tested in cooking environments to ensure long life without dimming.
- Three-speed electronic pushbutton control incorporates an LCD to display hood status for fan and lighting, filter clean reminder, Heat Sentry[™] and delay off.
- Broan Heat Sentry[™] detects excessive heat and adjusts the blower speed to prolong the life of the product and provide proper ventilation.
- Dishwasher-safe, deluxe micro-mesh filters provide highly efficient grease removal and patterned cover provides a decorative complement to the hood design. The filter clean reminder ensures they will always maintain a high level of capture.
- EZ1 brackets enable single-person installation in less than half the time of traditional methods.
- · ADA compliant, remote operation is possible using a standard UL approved wall switch (kit sold separately).
- Non-duct capable with use of charcoal filters, sold separately. Hidden louvers on top of hood exhaust away from cabinetry.



SPECIFICATIONS

400

< 0.5

120

Blower Normal CFM Sones Non-Ducted Charcoal Filter Volts Amps Duct 3-1/4" x 10" or 7" RD HPF30 (Type Xc)

1.4

* Kit sold separately.

Width

30"

36"

HAWRK3

HPF36 (Type Xd)

HPF42 (Type Xe)