## Product data sheet

ONSTRUCTION TYPE	
Range	•
Appliance width in inches	36
HEATING TYPE	
All electric	•
Cooktop	Induction
DESIGN	
Colour	CleanTouch Steel
Oven display	M Touch
CONVENIENCE FEATURES	
Wireless precision probe	•
Keeping warm	•
Crisp function	•
DPERATING MODES	
Convection Bake	•
Convection Roast	•
Booster	•
Booster	•
Defrost	•
Auto Roast	•
Maxi Broil	•
Maxi Broil Broil	•
Broil	•
Broil Intensive	•
Broil Intensive Moisture Plus	•
Broil Intensive Moisture Plus Slow Roasting	•
Broil Intensive Moisture Plus Slow Roasting Surround	· · · · ·
Broil Intensive Moisture Plus Slow Roasting Surround Browning	· · · · · ·

## COOKTOP FEATURES

Heating type	Induction
Number of induction cooking zones	5
Power level display	1 - 9
Residual heat indicator	•
PowerFlex cooking zones	4
PowerFlex cooking areas	2
Number of vario cooking zones	1 ring
USER CONVENIENCE	
Networking with Miele@home	•
Metal knobs	•
Backlit control knobs	•
Ergonomic swivel handle	•
Motorized lift-up control panel	•
Sabbath Program	•
Language Options	•
MyMiele	•
Clock synchronization	•
Time-of-day display	•
Date display	•
Timer	•
Safety shut-off	•
Programmable cooking duration	•
Actual temperature display	•
Recommended temperatures	•
Audible signal when desired temperature is reached	•
Favourites	•
Individual settings	•
Timed steam bursts	•
APPLIANCE DOOR	
CleanGlass door	•
Door contact switch	•
SoftClose oven door	•

Oven capacity in I	5.76 (163) ft³ (I)
Number of oven shelf levels	6
Number of halogen lights	double
TwinPower Convection Fans	•
CLEANING CONVENIENCE	
Stainless steel front with partial CleanTouch Steel finish	•
Self Clean oven	•
Catalyzer	•
Cooktop surface	Ceramic surface
EFFICIENCY AND SUSTAINABILITY	
Power-saving lighting circuit	•
Residual heat utilization	•
Rapid PreHeat	•
Rapid PreHeat	•
SAFETY	
Appliance cooling system with touch- cool fronts	•
Appliance cooling system with touch-	•
Appliance cooling system with touch-cool fronts	•
Appliance cooling system with touch- cool fronts  Safety shut-off	•
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock	•
Appliance cooling system with touch-cool fronts  Safety shut-off  System lock  Door contact switch	•
Appliance cooling system with touch-cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean	•
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean	•
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean  TECHNICAL DATA  Appliance width in mm	· · · · 36 1/8 (915)
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean  FECHNICAL DATA  Appliance width in mm  Appliance height in mm (min.)	• • • • • • • • • • • • • • • • • • •
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean  FECHNICAL DATA  Appliance width in mm  Appliance height in mm (min.)  Appliance height in mm (max.)  Dimensions in mm (depth) with	
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean  FECHNICAL DATA  Appliance width in mm  Appliance height in mm (min.)  Appliance height in mm (max.)  Dimensions in mm (depth) with bullnose	
Appliance cooling system with touch-cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean  FECHNICAL DATA  Appliance width in mm  Appliance height in mm (min.)  Appliance height in mm (max.)  Dimensions in mm (depth) with bullnose  Voltage in V	
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean  FECHNICAL DATA  Appliance width in mm  Appliance height in mm (min.)  Appliance height in mm (max.)  Dimensions in mm (depth) with bullnose  Voltage in V  Voltage convertible in V	• • • • • • • • • • • • • • • • • • •
Appliance cooling system with touch- cool fronts  Safety shut-off  System lock  Door contact switch  Door lock during SelfClean  FECHNICAL DATA  Appliance width in mm  Appliance height in mm (min.)  Appliance height in mm (depth) with bullnose  Voltage in V  Voltage convertible in V  Fuse rating in A	• • • • • • • • • • • • • • • • • • •

## ACCESSORIES SUPPLIED

Perforated Gourmet baking tray with PerfectClean	1
Anti-splash insert	1
Self Clean ready wire rack	2
Self Clean ready wire rack with rail system	1
Self Clean ready side racks	1