

System Format Active	Frequency Response (In-room, -6dB) 17 — 200 Hz	Maximum Usable SPL - Peak (CTA 2010-B, Z-weighted, half-space) 115 dB
Amplifier Output Instantaneous (RMS) 500 W	Amplifier Classification High-Efficiency Class-D	Bass Alignment Sealed
Low Pass Filter Frequency (-6dB) 32 — 200 Hz	Inputs Stereo Unbalanced RCA LFE Unbalanced RCA 12 V Trigger 3.5 mm mono jack	Input Impedance 47 kOhms
Phase Control 0° & 180° Toggle Switch	Equalisation DSP 3 pre-set modes: Impact, Movie, Music	Auto Music Sensing Auto On: Line Level >3 mV Auto Standby after 20 mins
Mains Input Voltage Universal Mains, 85 - 265 VAC, 50 - 60 Hz	Power Consumption (1/8th Maximum Output) 120 W	Drive Unit Complement 1x 12" (305 mm) High Linear-Excursion Triple Suspension Driver
External Dimensions with all accessories fitted (H x W x D) 385 x 371 x 401 mm (15 ^{1/8} x 14 ^{9/16} x 15 ^{13/16} ")	Weight 18.3 kg	Grille Cloth covered
Warranty 5 years		