

GENERAL			
Number of Channels	4	Amplifier Class	Class AB
Maximum Power Output	1000W	Maximum Power Output at 2 ff	250W x 4
Maximum Power Output at 4 ff	170W x 4	Nominal Power (RMS) Output at 2 ff	95W x 4
Nominal Power (RMS) Output at 4 ff	60W x 4	Nominal Power (RMS) Output - Bridged at 4 ff	190W x 4
Frequency Response	10Hz ~ 70kHz (+0dB , -3dB)	Total Harmonic Distortion (THD)	<0.05% (10W, 1kHz)
Signal-to-Noise (SN) Ratio	> 95dB	Fuse Rating	25Ax2

SPECIFICATIONS			
RCA Inputs	4-CH	Speaker Level Inputs	✔
Crossover Type	Adjustable HPF/LPF	Low-Pass Crossover Frequency	80 Hz
Low Pass Slope (dB/octave)	-12db/oct (A/B CH)	High-Pass Crossover Frequency	40-500 Hz
High-Pass Slope (dB/octave)	-12dB/oct	Bass Boost Frequency	50Hz
Bass Boost Level	0/6/12dB	Automatic Signal Sensing and Turn-On	✔
Hi-Volt Input Level Control	0.3V to 6.5V (RCA in), 3.0V to 26V (SP in)	Terminal Type	Screw
Load Impedance Allowance (Ω)	2 to 4	Bridgeable	✔
Protection Control System	✔	Dimensions (WxHxD)(inches)	356(W) X 60(H) X 215(D) mm
Warranty	1 Year		