

Specifications

Specifications (YAS-CU408)

Amplifier section

Maximum rated output power	
• Front L/R	50 W × 2ch

Speaker section

Front L/R	
• Type	Acoustic suspension type (non-magnetic shielding)
• Driver	4.6 cm (1-3/4") cone × 4
• Frequency response	160 Hz to 9 kHz
• Impedance	4 Ω (8 Ω × 2)

Tweeter	
• Driver	2.5 cm (1") dome × 2
• Frequency response	9 kHz to 23 kHz
• Impedance	4 Ω

Decoder

Supported audio signal (HDMI/optical input)	PCM (up to 5.1ch) Dolby Digital (up to 5.1ch) DTS Digital Surround (up to 5.1ch)
--	--

Input jacks

HDMI	1 (HDMI IN)
------	-------------

Digital (optical)	1 (TV)
Analog (3.5 mm stereo mini)	1 (ANALOG)

Output jacks

HDMI	1 (HDMI OUT (ARC))
------	--------------------

Other jacks

USB	1 (UPDATE ONLY)
LAN	1 (NETWORK)

Bluetooth

Function	Sink function (source device to this unit)
Bluetooth version	Ver 4.2
Supported profiles	A2DP, AVRCP
Supported codecs	Sink function: SBC, AAC
Bluetooth class	Bluetooth Class 2
Range (line-of-sight)	Approx. 10 m (33 ft)
Supported content protection method	SCMS-T (sink function)

[U.K. and Europe models]		
• Radio frequency	2402 MHz to 2480 MHz	
• Maximum output power (EIRP)	6.5 dBm (4.5 mW)	
Network		
Ethernet standard	100BASE-TX/10BASE-T	
Supported codecs	WAV (PCM format only) /AIFF/FLAC: up to 192 kHz ALAC: up to 96 kHz MP3/WMA/MPEG-4 AAC: up to 48 kHz	
PC client function		
AirPlay 2 supported		
Internet Radio		
Wi-Fi function		
• Wireless LAN standards:	IEEE 802.11 a/b/g/n/ac*	
	* 20 MHz channel bandwidth only	
• Radio frequency band	2.4 GHz/5 GHz	
• Available security method:	WEP, WPA2-PSK (AES), Mixed Mode	
[U.K. and Europe models]		
• Radio frequency	2402 MHz to 2482 MHz (20 MHz) 5170 MHz to 5250 MHz (20 MHz) 5250 MHz to 5330 MHz (20 MHz) 5490 MHz to 5710 MHz (20 MHz) 5735 MHz to 5835 MHz (20 MHz)	
• Maximum output power (EIRP)	19.2 dBm (83.2 mW) 5170 MHz to 5250 MHz (20 MHz): 21.5 dBm (141.3 mW) 5250 MHz to 5330 MHz (20 MHz): 21.8 dBm (151.4 mW) 5490 MHz to 5710 MHz (20 MHz): 24.1 dBm (257.0 mW) 5735 MHz to 5835 MHz (20 MHz): 13.5 dBm (22.4 mW)	
General		
Power supply		
• [U.S.A. and Canada models]	AC 120 V, 60 Hz	
• [Australia model]	AC 240 V, 50 Hz	
• [Europe, Asia, and Russia models]	AC 110 to 240 V, 50/60 Hz	
• [U.K. model]	AC 230 V, 50 Hz	
• [Taiwan model]	AC 110 V, 60 Hz	
• [China model]	AC 220 V, 50 Hz	
• [Korea model]	AC 220 V, 60 Hz	
Power consumption	30 W	

Standby power consumption

- [U.S.A., Canada and Taiwan models]
 - HDMI control off, network standby off 0.4 W
 - HDMI control off, network standby on (Wired/Wi-Fi/
Bluetooth) 1.6/1.8/1.7 W
 - HDMI control on, network standby off 0.7 W
 - HDMI control on, network standby on 2.2 W
 - [U.K. and Europe models and other models]
 - HDMI control off, network standby off 0.4 W
 - HDMI control off, network standby on (Wired/Wi-Fi/
Bluetooth) 1.6/1.8/1.7 W
 - HDMI control on, network standby off 0.7 W
 - HDMI control on, network standby on 2.2 W
-

Dimensions (W x H x D)

980 x 60 x 110.5 mm
(38-5/8" x 2-3/8" x 4-3/8")

Weight 2.7 kg (6 lbs)

NOTE

- The contents of this manual apply to the latest specifications as of the publishing date. To obtain the latest manual, access the Yamaha website then download the manual file.
- With an advanced energy saving design, this product achieves a low power consumption of not more than two watts when in Network Standby mode.

