

Product data sheet

CONSTRUCTION TYPE

Fully integrated dishwashers	•
45 cm dishwashers	•

DESIGN

Control panel colour	Stainless Steel.
Control panel version	Fully integrated fascia
Control type	Programme selector button
Display	3-digit 7-segment display
Display colour	Yellow

CONVENIENCE

Door closing aid	ComfortClose
Time left display	•
Delay start up to 24 h	•
In-operation indicator light	acoustic
Operating noise dB(A) re 1 pW	44

EFFICIENCY AND SUSTAINABILITY

Hot-water connection	•
Proven hygiene	•
ENERGY STAR® Most Efficient	•

EcoPower technology

-

QUALITY OF RESULTS

Fresh-water dishwasher

-

Recirculation turbothermic drying

-

WASH PROGRAMS

Automatic

-

Intensive 75°C

-

QuickIntenseWash

-

Sanitize

-

Rinse & Hold

-

CLEANING OPTIONS

Short

-

Extra clean

-

Extra dry

-

TECHNICAL DATA

Minimum niche height in mm

32 1/8 (815)

Appliance width in mm

17 3/4 (448)

Appliance height in mm

31 3/4 (805)

Appliance depth in mm

22 1/2 (570)

Appliance depth with door open in cm

45 7/8 (116.5)

Net weight in kg

90 (40.8)

Total rated load in kW

1.400

Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in cm	5 (1.50)
Length of water drain hose in cm	5 (1.50)
Length of power cable in m	4 (1.20)
Minimum niche width in mm	17 3/4 (450)
Niche depth in mm	21 3/4 (550)
Maximum niche width in mm	17 3/4 (450)
Maximum niche height in mm	34 3/4 (880)
Min. front panel weight in kg	2.0
Max. front panel weight in kg	8.0

BASKET DESIGN

Cutlery loading	Cutlery tray
Basket design	Comfort 45 cm
FlexCare cup rack	1

SAFETY

Waterproof system	•
Child lock	•