
GE Zoneline® Dry Air 25 Cooling and Electric Heat Unit with Corrosion Protection, 265 Volt



Model# AZ45E09EAP



- Perfect for high humidity climates Removes 20%-35% more moisture from the air than standard Zoneline air conditioners* (*Varies when comparing dehumidification rates of the 7,000/9,000/12,000 BTU base models to their dry air model counterparts)
- Cooling capacity 9,500 BTU
- Energy efficiency 12.1 EER
- Dehumidification 3.5 pints/hour
- Indoor fan CFM (high/low) 370/280
- Fresh air vent CFM (fully open high fan) 47
- Quiet operation Baked-on mastic sound barrier, cross flow blower and two DC fan motors create less noise to ensure comfort
- Corrosion resistant Extends life of the unit in sea coast areas/corrosive environments
- Heat & Freeze Sentinels Keeps the room from overheating or freezing
- Electronic temperature limiting Prevents expensive over-cooling or over-heating of the room
- - Electronic touch controls with LED display
- - R-410A refrigerant
- - SMC base pan
- Simplified structure Easy to maintain and service Have more questions? Please contact 1-800-626-2005

| FEATURES | |
|-----------------------------------|--|
| Sensible Heat Ratio | 58% |
| Chassis Type | Slide-In |
| Control Type | Coverless Backlit White LED Touch Controls |
| Corrosion Treated | Yes |
| Discharge Grille | 2-position |
| Electronic Micro Computer Control | Yes |
| Fan Cycle Switch | Yes |
| Fan Motor | 2 |
| Fan Speed Control | Yes |
| Fan Speed Selections | Hi/Low Cooling; Hi/Low Fan Only; Hi/Low Heating |
| Filter Type | Rigid Frame; Slide-Out |
| Heat - Cool | Yes |
| Louver Style | Reversible |
| Manual Vent Control | Hidden |
| Rotary Compressor | Yes |
| Temperature Limiting | Electronic 7-Step |
| Vent Control | 3-position |
| Dry Air | Yes |
| Venting Features | Concealed Manual Vent Control; Outdoor Vent Control - 3 Positions; Vent Air Filter |
| Zoneline Features | "Sleep" Mode; "Smart Fan" Fan Cycle Control; Auto Power Recovery; Automatic Indoor Frost Control; Central Desk Control Compatibility; Freeze Sentinel; Heat Sentinel; LCDI Power Cord (purchased separately); Proportional - Integral ID Airflow; Random Twist/Length Segment Tangential Blower; Remote Thermostat Compatibility; Universal Heaters; Weather Protected Electrical Components |
| Product Type | Packaged Terminal Air Conditioners (PTAC) |
| Temperature Range | 60 - 85 F |

GE Zoneline® Dry Air 25 Cooling and Electric Heat Unit with Corrosion Protection, 265 Volt



Model# AZ45E09EAP

APPROXIMATE DIMENSIONS (HxDxW)

• 16 in x 20 13/16 in x 42 in

CAPACITY

- Cooling BTUH (MIN) 9500.00 Btu
- Cooling EER (BTUH / Watt) 12.10
- CFM Indoor Fan High 370
- CFM Indoor Fan Low 260
- Dehumidification (pts./hr.) 3.50
- Vent CFM (high fan at zero ESP) 44

WARRANTY

- Parts Warranty Limited 1-year entire appliance;
 Limited 5-year sealed refrigerating system
- Labor Warranty Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
- Warranty Notes See written warranty for full details