

## Specifications

ANSI Certified - Yes

NSF Certified - Yes

Retail Packaging Height - 11 1/5"

Retail Packaging Width - 2 2/5"

Retail Packaging Depth - 2 3/10"

Volume - 0.43 Cu. Ft.

Alternate Part Number - 241791601; 242017801; 242017805; 242294401; RENEWULTRAWF; SULTRAWF

Country of Origin - Singapore

Filter Location - Back Top-right

Filter Type - Water Filter

Flow Rate - 0.5 gpm

Genuine Replacement Part - Yes

Installation Action - Push to lock

Item Package Quantity - 1

Maximum Operating Temperature - 100 F

Minimum Operating Temperature - 33 F

Minimum Working Pressure - 30 psi

Maximum Working Pressure - 100 psi

Product Weight - 1.14 lbs

Rated Capacity - 200 Gallons

Recommended Change Frequency // 3 - 6 Months

Installation and Care Instructions NOTICE: Review Frigidaire Refrigerator Use and Care Guide before installation and use of system. See fits models listing on Frigidaire.com. Fits all PureSource Ultra® and PureSource® 3 models manufactured by Frigidaire after 2009. 1. Push to release current filter, remove and discard. 2. Slide the new filter into the housing and push until it locks in place. 3. Run water through the dispenser for approximately 3 minutes, or 1.5 gallons, to prime the filter before use. Discard the water. 4. Replace every 6 months or 200 gallons (757 liters), whichever comes first.

Dishwasher Safe - No