Foster Ranges

Foster Milano Range 4b - 36"x 27" - 7162 900

HIGHLIGHTS



Performance and practicality.

The weighty enamelled cast iron grid has extraordinary dimensions, with a working surface up to 50% bigger compared to a normal domestic cooker hob.



Metal Knobs.

Exclusive and original the Foster metal knobs are an example of the strength and quality of the materials used. A distinctive feature that form an elegant uniformity in the kitchen.





Easy cleaning

The Foster Milano oven is supplied with a special antifingerprint treatment that makes cleaning the outside of the oven simple and quick.



Perfect safety

The ability to lock the oven door and the keyboard along with the four glass doors supplied with the oven are the best guarantees for safe and serene use

RANGETOP SPECIFICATONS

Model	Milano Rangetop 4f - 36" x 27"
Dimensions	35 55/64" x 27" x 35 53/64"
Maintop	AISI 304 Stainless Steel
Finish	Satin Finish
Grids	Enamelled cast iron
Hob controls	Knobs
Knobs	solid Metal
Safety	Safety valves
Total power	39,600 Btu/h
Burners	4
Dual	900-15,500 Btu/h
rapid	2,300-10,750 Btu/h
semirapid	1,300-9,100 Btu/h
auxiliary	900-5,000 Btu/h
Simmer ring	2
Simmer Rate	900 Btu/h
Technical requirments	
Electrical supply	120V 60Hz
Gas std setting	Natural Gas
LP Gas conversion	kit for all burners included
Optional accessories	Cast iron wok support
Certifications	CSA certified for US & Canada

COOKING FUNCTIONS



Dual ventilation



Delicate cooking



Convection broil



Defrost



Pizza (lower convection)



Keep warm (warm plus)



Convection roast



Proof warm



Bake

Broil



三/// Fast preheating



FOSTER MILANO INC. 6001 NORTH POWERLINE ROAD FORT LAUDERDALE, FLORIDA 33309 info@foster-us.com www.foster-us.com



Foster Ranges

Foster Milano Range 4b - 36"x 27" - **7162 900**

OVEN SPECIFICATIONS

Model	Milano 30" single SS
Oven Type	Multifunction Pyrolitic Oven
Door finishing	Satin finish Stainless Steel
cooking Functions	13
Control Type	Electronic
Temperature control	Electronic
Commands	2 knobs / 6 touch keys
Language	English
Special features	
Cleaning function	Pyrolitic self clean
Probe T control	yes
Preset/last uesd temperature memory	yes
Preheat bar (25%, 50%, 75%, 100%)	yes
Automatic fast preheat	yes
Sabbath mode	Yes
Safety	Keyboard lock, Child door lock
Temperature unit	°C/°F
Clock format	12/24 Hours
Cooking Functions	Pyrolitic Sel Clean with automatic door lock; Dual convection Bake; convection Broil; Convection Roast; Lower Convection (Pizza function); Bake; Broil; Delicate cooking; Defrost; Proof warm; Keep warm (warm plus); Light; Fast preheating.
Cavity	
Usable capacity	4,1CuFt
cavity finish	Dark gray pyrolitic enamel
Rack positions	6
Lighting	Triple asimmetrical halogen (20W) lighting
Broil upper heating element	3500 W (240 V)
Upper aux element	1032 W (240 V)
Concealed bake lower heating element	3000 W (240 V)
Convection element	2 x 1300 W (240 V)
Door	
door Glasses	4 heat resistant glasses
Inner side	Full glass
hinges	Heavy duty Steady Tilt
Handle	Satin finish Stainless steel handle

Technical Specifications

Electric supply	120/240VAC - 60Hz // 120/208VAC - 60Hz
Max Amp usage, power rating (240V,60Hz)	16,9 A - 3,84 kW
Max Amp usage, power rating (208V,60Hz)	17,5 A - 3,54 kW
cable + conduit	yes
certification	USA & CA (ETL)
Warranty	24 months
Installation & user manual:	EN, FR, SP
Delivered accessories	
Chromed racks	2
telescopic chromed rack	1
Enamelled grill set	1
Meat Probe	1



