## COMMERCIAL THROUGH RETAIL

## **PREP FOR CARD**

FRONT LOAD WASHERS AND TOP LOAD WASHERS







	Front Load Washer		
Product	Rear Control	Front Control	
Color	White		
Capacity - lb (kg)	21.5 (9.5)		
Cylinder Volume - cu.ft. (liters)	3.42 (96.8)		
Spin Speed G-Force (RPM)	440 (1200)		
Motor Size - HP (kw)	0.9 (0.67)		
Water Consumption Per Cycle - g (liter)*	13.68 (51.8)		
IWF (Water Factor) - gal/ft³ (liters/liter/cycle)*	4.0 (0.53)		
MEF <sub>32</sub> (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)*	2.20 (62.3)		
Available Water Temperatures	Cold, Warm, Hot		
Available Cycles	Normal, Synthetic, Delicate		
Electrical Requirements (v/Hz/Ph-Amp)	120/60/1-15 Amp		
Water Pressure - p.s.i (bar)	20-120 (1.4/8.3)		
Drain	Pump		
Cylinder Finish	Stainless Steel		
Net Weight - lb (kg)	260 (118)		
Shipping Weight - lb (kg)	270 (122.2)		
Width	34		
Shipping Dimensions Depth	30		
Approx - in			
Height	44.5		
Agency Approvals	cULus, ENERGY STAR® certified		
	SFNNYRSP116TW01	SFNNYASP116TW	

Product	Top Load Washer		
Color	White		
Capacity - lb (kg)	16 (7.3)		
Cylinder Volume - cu.ft. (lit	3.19 (90.3)		
Spin Speed G-Force (RPM)	150 (710)		
Motor Size - HP (kw)	0.5 (0.37)		
Water Consumption Per Cycle - g (liter)*	28.07 (106)		
IWF (Water Factor) - gal/ft (liters/liter/cycle)*	8.8 (1.18)		
MEF <sub>32</sub> (Modified Energy Factor ft³/kWh/cycle (Liters/kWh/cy			
Available Water Temperati	res Cold, Warm, Hot		
Available Cycles	Normal, Synthetic, Delicate		
Electrical Requirements (v/Hz/Ph-Amp)	120/60/1-15 Amp		
Water Pressure - p.s.i (bar)	20-120 (1.4/8.3)		
Drain	Pump		
Cylinder Finish	Stainless Steel		
Net Weight - lb (kg)	206 (93.4)		
Shipping Weight - lb (kg)	218 (98.8)		
	lth 28		
Shipping Dimensions De	oth 30		
Approx in	ght 45		
Agency Approvals	cULus		
Model No.	SWNNY2SP116TW01		

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Front Load Washer - Rear Control	26.875	43.875	27.73	14.6	24
Front Load Washer - Front Control	26.875	44.34	27.73	14.6**	24
Top Load Washer	25.625	43	28	51	-

## For Commercial Use Only

Supply inject kits available.

<sup>\*</sup> Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

<sup>\*\*</sup> For ADA compliance turn legs out from base 0.5 inches