

SOFIA PROFESSIONAL 30"

30" INDUCTION PROFESSIONAL RANGE

CODE ID

F6PIR304S1



- Easy Clean Ceramic Glass
- Power Boost Burner
- Pan Detection system
- Residual Heat Sensor

- Dual True Convection
- Soft Closing Door
- Self Clean Oven
- Multi-level cooking
- 1 Telescopic Rack
- Cool Touch Door
- Digital Controls
- Meat Probe
- Fast Pre-Heat

COLOR KIT

	STAINLESS STEEL		
	MATTE BLACK	RAL	9004
	GLOSSY BLACK	RAL	9004
	GLOSSY RED	RAL	3003
	GLOSSY WHITE	RAL	9016
	MATTE WHITE	RAL	9016
	MATTE GREY	RAL	9007
	MATTE SAGE	RAL	1306010

SPECIFICATIONS

COOKING SURFACE

4 Single Induction cooking zones
Elegant Ceramic glass surface
Premium induction technology for unsurpassed performance
Booster function for each cooking zone
Residual heat and Power-on Indicators
Melting and Simmering function
Pot Detection System
Child Lock Function
Failure Codes Indication
Automatic Heat-up Time

OVEN

Dual True Convection
Self-cleaning oven with Multifunction baking
Black Porcelain enamel interior
Cool to the touch soft closing door
Extra-large baking cavity and viewing area
3 Halogen lights for flawless visibility
Total capacity 123 lt
Total capacity 4.4 cu. ft.
2 chrome racks
1 telescopic rack
Enameled Broiler Pan

OVEN FUNCTIONS


Bake
Broil
Roast
Convection
True Convection
Warm / Proof / Dehydrate
Electronic cooking programmer
Meat Probe
Self-Clean
Sabbath Mode

OPTIONAL ACCESSORIES

PDRKIT30 ...	Color kit
F6BG30IND	Island trim
F6BG30STD	Standard trim
F6BG30HBT	High back trim
F6BG30BCI	Island trim
INDUKIT4	Induction plate adapters
FMTRP30	Telescopic rack

SOFIA

INDUCTION PROFESSIONAL RANGE



CODE ID	30" INDUCTION PROFESSIONAL RANGE - F6PIR304S1	
Series	600	
Finish	Professional Design - Stainless Steel	
CONTROL PANEL		
Control Type	6 Heavy Duty Knobs	
Oven Programming	Electronic with 6 Touch Keys	
Display: Clock - Temperature - Function	White LED	
Language	English / French / Spanish	
COOKTOP		
Type	INDUCTION	
Cooking Surface	Ceramic Glass	
INDUCTION COOKTOP FEATURES		
	Pot Detection System	Residual Heat Indication
	Melting Function	Simmering Function
	113°F / 45°C	158°F / 70°C
	Digital Display for Power Level	Booster/Fast Boil Function for Each Zone
	Failure Codes Indication	Power Levels: 1 to 9
	Cooling Fan System	Heat up time automatic
	Child Lock Function	Cooking Zones: 4
	Knob for power setting	
Burners types (Front-L) - Power (Max/Booster)	Inductor	9" (230 mm) 2300W / 3700W
Burners types (Rear-L) - Power (Max/Booster)	Inductor	6 - 1/2" (165 mm) 1400W / 2200W
Burners types (Center dual circuit) - Power (Max/Booster)	-	
Burners types (Center single circuit) - Power (Max/Booster)	-	
Burners types (Front-R) - Power (Max/Booster)	Inductor	7 - 3/4" (200 mm) 1850W / 3000W
Burners types (Rear-R) - Power (Max/Booster)	Inductor	7 - 3/4" (200 mm) 1850W / 3000W
OVEN		
Type	Electric Self-clean - Dual Convection (True Euro Conv.)	
Temperature Regulation	Electronic Control (min/max 170/550°F - 75/290°C)	
OVEN FUNCTIONS		
	Pyrolytic Self-Clean	Broil
	True Convection	Dehydrate
	Convection Broil	Thaw (Defrost)
	Convection Roast	Proof (Warm)
	Pizza (Lower Convection)	Keep warm (Warm Plus)
	Bake	Oven Lights
ELECTRIC OVEN FEATURES		
	Preset/Last Used Temperature Memory	Preheat Indicator (25%, 50%, 75%, 100%)
	Child Door Lock	Control Display Lock
	Fast Preheat	12/24 Hour Clock Formats
	Sabbath Mode	Temperature Display °C/°F
	Meat Probe	
OVEN DOOR(S)		
Oven Glass Window	Deep Embossed Extra Wide Window	
Door Cooling System	4 Heat Resistant Glasses	
Door Hinges - Soft-closing System	Heavy Duty Steady Tilt	
Handle Style	Stainless Steel Tube with Metal End caps	
OVEN CAVITY		
Total Capacity (lt)	123	
Total Capacity (cu. ft.)	4,34	
Usable Capacity (cbft)	4,1	
Cavity Enamel Color	Black	
Rack Positions	6	
Oven Lights	3x20W Halogen	
HEATING ELEMENTS (@240V)		
Broil Upper Heating Element	3500 W	
Upper Auxiliary Element	1032 W	
Concealed Bake Lower Heating Element	3000 W	
Convection Element	2 x 1300 W	
OVEN ACCESSORIES		
	2 Chrome Racks	1 Telescopic Chrome Rack
	1 Enameled Broiler Pan (basin + anti splash)	
DIMENSIONS/WEIGHT		
Overall dim - Width	29 - 3/4"	758 mm
Overall dim - Height (min - max)	36 - 3/8", 38 - 1/4"	923 mm - 972 mm
Overall dim - Depth	29 - 3/4"	756 mm
Gross Weight	311 lbs	141 kg
POWER / RATINGS (208/240 V, 60 HZ)		
kW / Amps rating at 120-240V, 60Hz	11kW - 45.8A	
kW / Amps rating at 120-208V, 60Hz	10kW - 48.5A	
Power Cable	Nema 14-50P	
INSTRUCTIONS FOR USE		
Use & Care Manual / Installation Manual	English / French / Spanish	