



## SUITABLE COOKING STYLE &amp; FEATURES:



Minimal

Everyday

Heavy-Duty

Colors:  
(Handle & Knob)

PRG30

HAUSPRO SINGLE OVEN GAS RANGE

SIZES: 30"

## PRODUCT DESCRIPTION



The Hauslane HausPro 30" gas range gives you the power, space, and flexibility to cook your way. Up to four burners give you heat from 1,000 BTUs for gentle simmering to a blazing 20,000 BTUs for that steakhouse sear. A gas powered oven delivers intense, efficient heating for perfectly roasted meals.

## WHAT'S INCLUDED

Surface Grates (3), Surface Burners and Caps (4), Anti-Tip Bracket Kit (1), LP Conversion Kit (1), Microfiber Cloth (1), Hex Tool (1)

## OVERALL PRODUCT DIMENSIONS (WxDxH)

30" x 27 5/16" x 36"

## WARRANTY

5-Year Parts Protection  
5-Year Labor Warranty  
Limited-Lifetime Burner Warranty



## FEATURES &amp; BENEFITS:

## UNLEASH YOUR CULINARY CREATIVITY:

Up to 4 burners ranging from 1,000 to 20,000 BTUs give you precise control for everything from gentle simmering to steakhouse-style searing—paired with a gas oven that ensures efficient, flavourful baked meals.

## BAKE TO PERFECTION WITH TRUE CONVECTION:

4.2 cu. ft. Ovens circulate hot air evenly for faster, more consistent results. Five rack positions and up to four telescopic racks let you cook multiple dishes at once (2 racks on 30" and 36" models / 4 racks on 48" models).

## COOK SAFELY AND COMFORTABLY:

Triple-layer insulated oven doors stay cooler to the touch, protecting curious hands while locking in heat.

Textured grip handles prevent slips. Telescopic racks glide smoothly for safe, burn-free access.

## FITS SEAMLESSLY INTO YOUR KITCHEN:

Adjustable height (36" - 37 1/2") for a flush fit, heavy-duty easy-slide grates for moving pots without lifting, and a convertible setup that works with both natural gas and LP.





## SPEND LESS TIME CLEANING:

Stainless steel finish resists fingerprints and smudges keeping cleanup quick and stress-free.

## COOK WITH CONFIDENCE:

Backed by a limited-lifetime burner warranty and a 5-year parts and labor oven warranty for lasting peace of mind.


## TECHNICAL DRAWING



## RANGE PLACEMENT MEASUREMENTS

<b>W</b> CABINET CUT OUT DIMENSIONS (WxDxH)	30 1/4" x 24 3/4" x 36"
<b>1</b> STANDARD DEPTH OF CABINET ABOVE COOKTOP	13" (330 mm)
<b>2</b> DEPTH FROM REAR OF CHASSIS TO FRONT OF CONTROL PANEL	27 5/16" (694 mm)
<b>3</b> MINIMUM CLEARANCE (COUNTERTOP TO CABINET, BOTH SIDES OF RANGE)	18" (457 mm)
<b>4</b> COOKTOP SIDE TO CABINET CLEARANCE (ADJACENT WORKING AREAS)	6" (152 mm)
<b>5</b> MINIMUM CLEARANCE FROM COOKTOP TO VENTILATION HOOD	30" - 36" (762 - 914 mm) Depending on Your Hood Model
<b>6</b> COOKTOP HEIGHT FROM FLOOR (TO COOK SURFACE)	37 1/2" to 39" (953 - 991 mm) Depending on Leveling and Installation Height
<b>7</b> GAS AND ELECTRICAL CONNECTION AREA (MAXIMUM DEPTH)	Max Depth of Gas / Electric Rough-in Area: 2 13/16" (71 mm) from the Rear Wall

<b>8</b> GAS & ELECTRICAL ZONE (WIDTH)	22" (Approx.)
<b>9</b> GAS AND ELECTRICAL CONNECTION AREA (MAXIMUM HEIGHT)	Vertical Space from Floor to Gas / Electric Rough-in Area: 4 1/2" (114 mm) from the Floor
<b>A</b> GAS AND ELECTRICAL HOOKUP ZONE (WxH)	30 1/4" x 15"



## KNOB &amp; HANDLE COLORS

STAINLESS STEEL  
PRG30-SSBLACK STAINLESS STEEL  
PRG30-BSROSE GOLD  
PRG30-RGSATIN BRASS  
PRG30-GDMATTE BLACK  
PRG30-FB

## OVERALL SPECIFICATIONS

SIZE	30"
STYLE	Pro Style
BURNER TYPE	Sealed Burners
TYPE OF GRATE	Continuous
AUTO-REIGNITION	Yes
CONVECTION TYPE	Single Fan
OVEN RACK POSITIONS	5
NUMBER OF RACKS	2
OVEN LIGHT BULB	2 Halogen Light Bulbs
CONTROL	Mechanical Knob
PANEL LIGHT COLOR	Blue
POWER CORD LENGTH	70"
CONSTRUCTION	Freestanding
WATTAGE (kW)	1.08
VOLTAGE (V)	120
AMPERAGE (A)	9
FREQUENCY (Hz)	60
PLUG TYPE	3-prong
ELECTRICAL SERVICE	15-Amp Dedicated Circuit
GROSS WEIGHT, LBS.	287
NET WEIGHT, LBS.	218
ADJUSTABLE HEIGHT	1 1/2" Max


ACCESSORIES	Wok Ring (WOK-01) Sold Separately, Griddle (GRD-01) Sold Separately
-------------	---

## GAS TIPS &amp; GAS REQUIREMENTS

FUEL TYPE	NG	LPG
<b>BURNER A (TIP)</b>	1.36 (2) + 0.73	0.89 (2) + 0.53
<b>BURNER B (TIP)</b>	1.36	0.90
<b>BURNER C (TIP)</b>	1.79	1.16
<b>BURNER D (TIP)</b>	1.36	0.90
<b>30" BROIL (UPPER TIP)</b>	1.42	0.94
<b>30" BAKE (BOTTOM TIP)</b>	2.13	1.40
<b>SUPPLY PRESSURE</b>	5" (12.5 mb)	10" (25 mb)
<b>MINIMUM LINE PRESSURE</b>	7" (17.5 mb)	11" (27.4mb)
<b>MAXIMUM REGULATOR PRESSURE</b>	14" (34.9 mb), 0.5 psi (3.5 kPa)	14" (34.9 mb), 0.5 psi (3.5 kPa)

## COOKTOP PERFORMANCE

NUMBER OF BURNERS	4
BURNER A MAX - MIN (BTUS)	20,000 - 1,000
BURNER B MAX - MIN (BTUS)	9,000 - 1,500
BURNER C MAX - MIN (BTUS)	15,000 - 2,400
BURNER D MAX - MIN (BTUS)	9,000 - 1,500



## OVEN SPECIFICATIONS

OVEN COOKING MODES	Bake, Conv Bake, Broil
CONVERTIBLE	Natural Gas / Liquid Propane
30" OVEN BROIL (BTU)	10,000
30" OVEN BAKE (BTU)	22,000
SELF CLEAN	N/A
SABBATH MODE	N/A
AIR FTY	N/A
OVEN CAPACITY	4.2 cu. ft.
PRIMARY OVEN INTERIOR (WxDxH)	24 7/8" x 17 3/4" x 16"
SECONDARY OVEN INTERIOR (WxDxH)	N/A





## SUITABLE COOKING STYLE &amp; FEATURES:



Minimal

Everyday

Heavy-Duty

**22K BTUs**  
 BAKE OVEN

**20K BTUs**  
 BURNER

 5 YEAR  
 WARRANTY

 CONVECTION  
 FAN

 TELESCOPIC  
 RACK

**Colors:**  
 (Handle & Knob)
**PRD30****HAUSPRO SINGLE OVEN DUAL FUEL RANGE****SIZES: 30"****PRODUCT DESCRIPTION**

The Hauslane HausPro 30" dual fuel range gives you the power, space, and flexibility to cook your way. Up to four burners give you heat from 1,000 BTUs for gentle simmering to a blazing 20,000 BTUs for that steakhouse sear. A dry-heat electric oven delivers the most reliable high-heat settings. No half-baked meals are found here!

**FEATURES & BENEFITS:****UNLEASH YOUR CULINARY CREATIVITY:**

Up to 4 burners ranging from 1,000 to 20,000 BTUs give you precise control for everything from gentle simmering to steakhouse-style searing—paired with a gas oven that ensures efficient, flavourful baked meals.

**BAKE TO PERFECTION WITH TRUE CONVECTION:**

4.2 cu. ft. Ovens circulate hot air evenly for faster, more consistent results. Five rack positions and up to four telescopic racks let you cook multiple dishes at once (2 racks on 30" and 36" models / 4 racks on 48" models).

**COOK SAFELY AND COMFORTABLY:**

Triple-layer insulated oven doors stay cooler to the touch, protecting curious hands while locking in heat.

**WHAT'S INCLUDED**

Surface Grates (3), Surface Burners and Caps (4), Anti-Tip Bracket Kit (1), LP Conversion Kit (1), Microfiber Cloth (1), Hex Tool (1)

**OVERALL PRODUCT DIMENSIONS (WxDxH)**

30" x 27 5/16" x 36"

**WARRANTY**

5-Year Parts Protection  
 5-Year Labor Warranty  
 Limited-Lifetime Burner Warranty



Textured grip handles prevent slips. Telescopic racks glide smoothly for safe, burn-free access.

**FITS SEAMLESSLY INTO YOUR KITCHEN:**

Adjustable height (36" - 37 1/2") for a flush fit, heavy-duty easy-slide grates for moving pots without lifting, and a convertible setup that works with both natural gas and LP.





**SPEND LESS TIME CLEANING:**

Stainless steel finish resists fingerprints and smudges keeping cleanup quick and stress-free.

**COOK WITH CONFIDENCE:**

Backed by a limited-lifetime burner warranty and a 5-year parts and labor oven warranty for lasting peace of mind.


## TECHNICAL DRAWING



## RANGE PLACEMENT MEASUREMENTS

<b>W</b> CABINET CUT OUT DIMENSIONS (WxDxH)	30 1/4" x 24 3/4" x 36"
<b>1</b> STANDARD DEPTH OF CABINET ABOVE COOKTOP	13" (330 mm)
<b>2</b> DEPTH FROM REAR OF CHASSIS TO FRONT OF CONTROL PANEL	27 5/16" (694 mm)
<b>3</b> MINIMUM CLEARANCE (COUNTERTOP TO CABINET, BOTH SIDES OF RANGE)	18" (457 mm)
<b>4</b> COOKTOP SIDE TO CABINET CLEARANCE (ADJACENT WORKING AREAS)	6" (152 mm)
<b>5</b> MINIMUM CLEARANCE FROM COOKTOP TO VENTILATION HOOD	30" - 36" (762 - 914 mm) Depending on Your Hood Model
<b>6</b> COOKTOP HEIGHT FROM FLOOR (TO COOK SURFACE)	37 1/2" to 39" (953 - 991 mm) Depending on Leveling and Installation Height
<b>7</b> GAS AND ELECTRICAL CONNECTION AREA (MAXIMUM DEPTH)	Max Depth of Gas / Electric Rough-in Area: 2 13/16" (71 mm) from the Rear Wall

<b>8</b> GAS & ELECTRICAL ZONE (WIDTH)	22" (Approx.)
<b>9</b> GAS AND ELECTRICAL CONNECTION AREA (MAXIMUM HEIGHT)	Vertical Space from Floor to Gas / Electric Rough-in Area: 4 1/2" (114 mm) from the Floor
<b>A</b> GAS AND ELECTRICAL HOOKUP ZONE (WxH)	30 1/4" x 15"



## KNOB &amp; HANDLE COLORS

STAINLESS STEEL  
PRD30-SSBLACK STAINLESS STEEL  
PRD30-BSROSE GOLD  
PRD30-RGSATIN BRASS  
PRD30-GDMATTE BLACK  
PRD30-FB

## OVERALL SPECIFICATIONS

SIZE	30"
STYLE	Pro Style
BURNER TYPE	Sealed Burners
TYPE OF GRATE	Continuous
AUTO-REIGNITION	Yes
CONVECTION TYPE	Single Fan
OVEN RACK POSITIONS	5
NUMBER OF RACKS	2
OVEN LIGHT BULB	2 Halogen Light Bulbs
CONTROL	Mechanical Knob
PANEL LIGHT COLOR	Blue
POWER CORD LENGTH	59"
CONSTRUCTION	Freestanding
WATTAGE (kW)	4.32
VOLTAGE (V)	240
AMPERAGE (A)	18
FREQUENCY (Hz)	60
PLUG TYPE	4-prong
ELECTRICAL SERVICE	25-Amp Dedicated Circuit
GROSS WEIGHT, LBS.	297
NET WEIGHT, LBS.	229
ADJUSTABLE HEIGHT	1 1/2" Max


ACCESSORIES	Wok Ring (WOK-01) Sold Separately, Griddle (GRD-01) Sold Separately
-------------	---

## GAS TIPS &amp; GAS REQUIREMENTS

FUEL TYPE	NG	LPG
<b>BURNER A (TIP)</b>	1.36 (2) + 0.73	0.89 (2) + 0.53
<b>BURNER B (TIP)</b>	1.36	0.90
<b>BURNER C (TIP)</b>	1.79	1.16
<b>BURNER D (TIP)</b>	1.36	0.90
<b>30" BROIL (UPPER TIP)</b>	N/A	N/A
<b>30" BAKE (BOTTOM TIP)</b>	N/A	N/A
<b>SUPPLY PRESSURE</b>	5" (12.5 mb)	10" (25 mb)
<b>MINIMUM LINE PRESSURE</b>	7" (17.5 mb)	11" (27.4mb)
<b>MAXIMUM REGULATOR PRESSURE</b>	14" (34.9 mb), 0.5 psi (3.5 kPa)	14" (34.9 mb), 0.5 psi (3.5 kPa)

## COOKTOP PERFORMANCE

NUMBER OF BURNERS	4
BURNER A MAX - MIN (BTUS)	20,000 - 1,000
BURNER B MAX - MIN (BTUS)	9,000 - 1,500
BURNER C MAX - MIN (BTUS)	15,000 - 2,400
BURNER D MAX - MIN (BTUS)	9,000 - 1,500



## OVEN SPECIFICATIONS

OVEN COOKING MODES	Bake, Conv Bake, Broil
CONVERTIBLE	Natural Gas / Liquid Propane
30" OVEN BROIL (kW)	3.2
30" OVEN BAKE (kW)	2.8
SELF CLEAN	N/A
SABBATH MODE	N/A
AIR FTY	N/A
OVEN CAPACITY	4.2 cu. ft.
PRIMARY OVEN INTERIOR (WxDxH)	24 7/8" x 17 3/4" x 16"
SECONDARY OVEN INTERIOR (WxDxH)	N/A

