



## Revillusion®

24" Built-in Electric Firebox  
/ Fireplace Insert

RBF24DLX  
Herringbone Brick



Easily update and finish an existing fireplace with Revillusion technology.

Revillusion® is a completely new way of looking at fireplaces, and changing the standard for electric. A clear view through the lifelike flames, to the full brick interior, captures the charm of a wood-burning fireplace. Enjoy the look of a fireplace cut straight from the pages of a magazine by choosing Revillusion®; clearly a better fireplace.

Revillusion®  
by Dimplex

## Revillusion® 24" Built-in Electric Firebox / Fireplace Insert

## RBF24DLX Herringbone Brick



### Deluxe Features

- ComfortSaver® Heating System**  
The patented ComfortSaver® ceramic heating system uses 11% less energy than the leading quartz infrared heater by automatically adjusting fan speed and heater wattage to safely and precisely match the requirements of the room.
- Eco Boost**  
When Eco Boost is activated heater runs in a reduced wattage range.
- Flame Speed**  
Allows you to adjust the speed of the flame to create the perfect atmosphere to suit your mood or room.
- Glass Pane Included**

120 V | 1,500 W | 5,118 BTU

### Also available in Weathered Concrete - RBF24DLXWC



### Features

- Revillusion® Flame Technology**  
Flames are larger, brighter and more random, appearing from within the logs.
- Mirage™ Flame Panel**  
Partially frosted acrylic panel is clearly better than a mirror, showing only dazzling flames and no reflections.
- ThruView™ Full-depth Design**  
See clear through the flames to the back of the firebox for a more authentic experience.
- Mood Lighting**  
Customize the firebox glow with a choice of warm hues, plus midnight mode.
- Color Enhancement**  
Adjust the flame base color to red or blue.
- Realogs® Plus**  
A full grate of life-size hardwood-cast logs, tiered for greater depth.
- Full Surround Firebox**  
More authentic day or night; 270-degree surround with natural soot markings.
- Brightness and Flicker**  
Adjust light level to suit the room and choose flicker effect for enhanced firelight.
- Ambient Light Sensor**  
Automatically adjusts firebox light to suit the room day to night.
- All-season Flames**  
Enjoy the unique charm of a fireplace 365 days a year using the flames without the heat.
- Just Plug It In / Direct-wire**  
Simply plug into any standard household outlet for instant ambiance. Can be hardwired to a 120 volt circuit for a seamless look.

Model #	Description	Lbs / Kg	UPC	Wty <sup>1</sup>	Carton Dimensions (WxHxD)		Cube	
					Inches	cm	ft <sup>3</sup>	m <sup>3</sup>
RBF24DLX	24" Built-in Electric Firebox - Herringbone brick interior	58.2 / 26.4	781052 120655	2 yrs.	29-3/8 x 28-1/8 x 16-3/8	74.4 x 71.2 x 41.6	7.83	0.22
RBF24DLXWC	24" Built-in Electric Firebox - Weathered concrete interior	58.2 / 26.4	781052 129832	2 yrs.	29-3/8 x 28-1/8 x 16-3/8	74.4 x 71.2 x 41.6	7.83	0.22
RBFL24BR	Birch Log Set	15 / 6.8	781052 130005	2 yr.	25-7/8 x 17-1/2 x 15	65.5 x 44.2 x 38.1	3.90	0.11
RBFL24FC	Fresh Cut Log Set	15 / 6.8	781052 129955	2 yr.	25-7/8 x 17-1/2 x 15	65.5 x 44.2 x 38.1	3.90	0.11
RBF24TRIM36	36" Installation Trim	15.7 / 7.1	781052 123595	1 yr.	39-1/8 x 36-1/4 x 4-5/8	99.2 x 92.0 x 11.5	3.80	0.10
RBF24TRIM40	40" Installation Trim	17.7 / 8.0	781052 123618	1 yr.	43 x 36-1/4 x 4-5/8	109.2 x 92.0 x 11.8	1.01	0.11


Specifications, finishes and dimensions are subject to change. <sup>1</sup>Limited warranty. ©2018 Glen Dimplex Americas

SE-367-R06-091119

## Revillusion® 24" Built-in Electric Firebox / Fireplace Insert

## RBF24DLX Herringbone Brick

### Accessories



RBF24TRIM36  
- 36" Black Installation Trim



RBF24TRIM40  
- 40" Black Installation Trim



RBFL24BR - Birch Log Set  
Dimensions:  
18-1/2" W x 10-7/8" H x 11" D  
(46.8 cm x 27.4 cm x 27.9 cm)



RBFL24FC - Fresh Cut Log Set  
Dimensions:  
18-1/2" W x 10-7/8" H x 11" D  
(46.8 cm x 27.4 cm x 27.9 cm)

### Framing Dimensions:

RBF24DLX		
A	B	C
12-1/2" (31.8 cm)	24-5/8" (62.5 cm)	22-3/4" (59.3 cm)
D	E	F
47-3/4" (121.2 cm)	33-3/4" (85.7 cm)	33-3/4" (85.7 cm)

**NOTE:** The materials used for the finished surround must be cut to precise dimensions as the 1/2" (1.3 cm) self-trimming flange is only to create a finished appearance.

### Firebox Insert Trim Dimensions:

