# SONY

#### VPL-VW385ES

### **4K HDR Home Theater Projector**

Experience breathtaking 4K HDR clarity and brightness in every living space. With a dynamic contrast ratio of 200,000:1 and Advanced Iris every scene springs to life with finer detail, realism, and deep blacks. Picture Position Memories lets you quickly watch movies in the ideal screen format.



- Full 4K resolution with 4096 x 2160 pixels
- Three SXRD™ imagers for full color brightness
- Advanced Reality Creation for upscaling and sharpening images without sharpening picture noise<sup>1</sup>
- 200,000:1 dynamic contrast with Advanced Iris makes every scene spring to life.
- High brightness of 1,500 Lumens
- Enjoy High Dynamic Range (HDR) content in various formats
- Picture Position Memories store your settings
- View clear sharp images with Motionflow<sup>™</sup> XR technology
- Enjoy gaming and other types of content in 4K HDR
- TRILUMINOS™ Display for wider array of rich colors

#### **Features**

#### Native 4K resolution for lifelike pictures.

With more than four times the resolution of Full HD¹, native 4K offers 8.8 million pixels (4096 x 2160) for a picture that's so incredibly lifelike, it's like looking at the real thing.

# **SXRD™ Imagers times 3**

Separate imagers for Red, Green and Blue channels give you all 8.8 million pixels in full, rich color at every instant

#### **HDR Compatible**

Take full advantage of the latest content produced with HDR (High Dynamic Range) for extremely wide contrast range with an even higher range of brightness levels and volume of colors.

# High brightness and contrast

With an impressive 1,500 lumens brightness, 4K images are clear with bright highlights and rich, deep blacks – even in well-lit rooms.

#### 200,000:1 dynamic contrast with Advanced Iris

A dynamic contrast ratio of 200,000:1 with Advanced Iris makes every scene spring to life with finer detail, realism, and deep blacks.

#### Reality Creation upscales your favorites.<sup>2</sup>

Upscale your existing Blu-ray Disc<sup>™</sup> and DVD movies to near 4K quality. <sup>2</sup> The super-resolution Reality Creation 4K upscaler analyzes every pixel in any direction, then employs a digital signal processing algorithm to map pixels against an ever-evolving picture patterning database, compiled from over 10 years of expertise, to enhance colors, contrast, and textures without enhancing image

# Action stays smooth and sharp with MotionFlow™

Whatever you're watching, you'll enjoy a silk-smooth and razor-sharp on-screen look in fast-moving action sequences with Motionflow™. This innovative technology creates and inserts extra frames between the original frames by first comparing key visual factors on successive frames, then calculating the split second of missing action in the sequences. True Cinema 24p mode mimics true movie projection for cinema purists.

#### Picture position Memory stores your settings

Lens focus, zoom, and shift, as well as aspect ratio and blanking settings for up to five screen formats can be stored for easy recall. Picture Position Memories remember these settings so you can quickly watch movies in theideal screen format. Match aspect ratios, including 16:9 and Cinemascope, and store these settings in the projector.

# Colors come alive with TRILUMINOS™ Display

Discover true-to-life colors and tones. The VPL-VW385ES incorporates TRILUMINOS™ Display color, reproducing more tones and textures than a standard projector system. Hard-to-reproduce crimson reds, aqua blues, and emerald greens are displayed beautifully, so landscapes and seascapes look more vivid. Faces look better, too, with skin tones more faithfully reproduced.

#### Enjoy all types of content in 4K HDR.

4K HDR 60p 10bit (for HDR10/HLG) compatible so you can enjoy gaming and other high frame rate content in 4K HDR.

# Support for latest standards.

The VPL-VW385ES can project content at up to 60 frames per second (fps) in 4K for even smoother images with superior color and realism. Both HDMI inputs support HDCP 2.2 so you can enjoy more of the latest 4K content services.<sup>4</sup>

#### Watch for longer with a 225 W high-pressure lamp.

Enjoy up to 6000 hours of viewing time (in low mode) from a long-lasting mercury lamp. This means fewer lamp swaps, simpler maintenance, and lower running costs.

#### Flexible home installation with wide zoom and shift lens

The powered zoom lens with a 2.1x zoom ratio and wide lens shift range gives greater installation flexibility in any room size, even with a high ceiling.

#### Built-in 3D transmitter synchronizes entertainment<sup>3</sup>

A built-in 3D transmitter synchronizes the optional glasses with the projector, so you can start watching 3D movies quicker. Upscale 2D films to 3D and enjoy classic movies in a whole new dimension, or watch anamorphic images and 3D films simultaneously without changing the lens. High-emission power gives you a strong signal anywhere in the room.

# **Specification**

| Light output  |  |                         |  |
|---|--|-------------------------|--|
| 2D [lm]   | 1,500 lm                                 |                         |  |
| Display device                                      |  |                         |  |
| Display device                                      | SXRD 0.74" x3                            |                         |  |
| Effective picture elements                          | 26,542,080 pixels                        |                         |  |
| Resolution  | 4096x2160                                |                         |  |
| Drive [Hz]  | 120                                      |                         |  |
| System  | Digital                                  |                         |  |
| Projection lens                                     |  |                         |  |
| Projection lens                                     | Powered                                  |                         |  |
| Zoom  | Zoom ratio: x 2,1                        |                         |  |
| 200111  | Wide:1,38                                |                         |  |
| Throw ratio   | Tele: 2,83                               |                         |  |
|   | V: Powered                               |                         |  |
|   | Max. range: +85%/-80%                    |                         |  |
| Lens shift  |  |                         |  |
|   | H: Powered                               |                         |  |
|   | Max. range: 31%"                         |                         |  |
| Projection image size                               |  |                         |  |
| Projection image size                               | 60"-300"                                 |                         |  |
| Light source  |  |                         |  |
| Power   | 225W                                     |                         |  |
| Туре  | UHP                                      |                         |  |
| Life  | 6,000 h                                  |                         |  |
| Acoustic noise                                      |  |                         |  |
| Low mode  | 26 dB                                    |                         |  |
| Operating conditions                                |  |                         |  |
| Operating temp.                                     | /1°E to 05°E (5°C to 35°C)               |                         |  |
| , ,   | 41°F to 95°F (5°C to 35°C)               |                         |  |
| Storage Temp.                                       | -4°F to +140°F (-20°C to +60°C)          |                         |  |
| Operating Humidity                                  | 35 to 85%                                |                         |  |
| Storage Humidity                                    | 10 to 90%                                |                         |  |
| Ventilation   | Intake: Back / Exhaust: Front            |                         |  |
| Installation  | Ceiling/Table/Front/Rear                 |                         |  |
| Power   | A C400 240V 50/50 V                      |                         |  |
| Power consumption                                   | AC100-240V 50/60 Hz                      |                         |  |
| Power consumption (In Operation)                    | High 120V: 350W                          |                         |  |
|   | High 220V-240V: 350W                     |                         |  |
| Power Consumption (in Standby)                      | Standby: 0.3 W<br>Network Standby: 1,0 W |                         |  |
| Power Requirements                                  | AC100-240V 50/60 Hz                      |                         |  |
| ·   | AC100-2407 30/00 HZ                      |                         |  |
| Display Performance                                 | 1  | 11                      |  |
| Display resolution                                  | Video                                    | Up to 4096/60p          |  |
| Bit depth (IN)@1920*1080                            | YUV422                                   | 12                      |  |
| Frame Rate@ 23.98/24/50/59.54/60                    | RGB444                                   | 12                      |  |
| 114111C Nate & 23.36/24/30/33.34/00                 | Deep Color                               | Yes                     |  |
| Dit donth (INI)@4000*2400                           | RGB444                                   | 12 (422 10bit)          |  |
| Bit depth (IN)@4096*2160<br>Frame Rate@ 23.98/24    | YUV422                                   | 12 (422 10bit)          |  |
| Frame Rate@ 23.98/24                                | Deep Color                               | Yes                     |  |
| Bit depth (IN)@4096*2160<br>Frame Rate@ 50/59.54/60 | YUV420                                   | 12 (8 bit)              |  |
| HDR   | EOTF Signal Compatibility                | HDR10/HLG               |  |
|   | EOTF Signal Display                      | HDR10/HLG               |  |
|   | Auto Detect Function                     | Yes (Both EOTF&BT.2020) |  |
| Terminals   |  |                         |  |
| HDMI  | 2  |                         |  |
| Ver.  | 2.0b                                     |                         |  |
| HDCP  | all inputs: 2.2                          |                         |  |
|   | RS-232C                                  | 1                       |  |
| Network & Control                                   | IR IN                                    | 1                       |  |
|   | Trigger                                  | 2                       |  |
|   | 30                                       |                         |  |

|                               | LAIN   | . //           |  |
|-------------------------------|--|----------------|--|
| Others                        | USB  | 1 (for Update) |  |
| Network                       |  |                |  |
|                               | Yes  |                |  |
|                               | PJ Talk2   | Yes            |  |
|                               | Advertisement (SADP)   | Yes            |  |
| IP control                    | Crestron Connected   | Yes            |  |
|                               | AMX DDDP   | Yes            |  |
|                               | C4 SDDP  | Yes            |  |
|                               | ADCP   | Yes            |  |
| Other Functions               |  |                |  |
| 3D                            | Active   |                |  |
| Picture Modes                 | 9  |                |  |
| Reality Creation              | Yes  |                |  |
| Color Temp.                   | D93/D75/D65/D55/Custom1-5  |                |  |
| Smooth Gradation              | H/M/L/Off (2K)   |                |  |
| Motion Flow                   | Yes (2K)   |                |  |
| Contrast Enhancer             | H/M/L/Off  |                |  |
| Gamma Correction              | 1-10 / Off   |                |  |
| Color Correction              | On/Off   |                |  |
| Clear White                   | H/L/Off  |                |  |
| X.V. Color                    | Yes  |                |  |
| Color Space                   | BT.709/BT.2020/CS1-3/Custom  |                |  |
| Triluminos Display            | Yes  |                |  |
| Aspect                        | 6  |                |  |
| Blanking                      | Yes  |                |  |
| Anamorphic                    | 3D:Yes   |                |  |
| 3D Brightness                 | Bright/Standard  |                |  |
| Simulated 3D                  | Yes  |                |  |
| HDMI Dynamic Range            | Yes  |                |  |
| HDMI Signal Format            | Standard/Enhanced  |                |  |
| Panel Alignment               | Shift/Zone: 1/10 dot   |                |  |
| Lens Center Design            | Yes  |                |  |
| Other Product Relationships   |  |                |  |
| ·                             | Remote Control (RM-PJ24)   |                |  |
|                               | Size AA (R6) manganese batteries (2)                                       |                |  |
|                               | AC Power cord (Local (Ex.US/CN))   |                |  |
| Supplied Accessories          | Operating Instruction (CD-R)   |                |  |
|                               | Quick Reference Manual   |                |  |
|                               | Safety Regulation  |                |  |
|                               | Warranty Card  |                |  |
| Optional accessories          | TDG-BT500A   |                |  |
| Weight and Measurements /Main |  |                |  |
| Dimensions (WxHxDcm)(Approx.) | 19 1/2 x 7 7/10 x 18 13/50 inches  |                |  |
| incl.projecting parts         | $(496 \times 195 \times 464 \text{ mm})$ (W x H x D) (without protrusions) |                |  |
| Weight (kg)(Approx.)          | 31 lb (14 kg)  |                |  |

1. 4096 x 2160 resolution

Network & Control

 $2. \ \ Upscaled, simulated and enhanced \ 4K images \ will \ vary \ based \ on \ source \ content.$ 

LAN

- 3. 3D glasses (TDG-BT500A) are optional; requires 3D content, a 3D player, and an HDMI cable (at least 10.2 Gbps).
- 4. Requires HDMI®cable sold sep. "

© 2017 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All screen images simulated. Sony, SXRD, and Motionflow are trademarks of Sony Corporation. HDMI is a trademark of HDMI Licensing LLC. All other trademarks are trademarks of their respective owners.