

FEATURES & BENEFITS



MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-29RB-00A	115 / 60	Field Reversible	Black Solid	89 lb
U-29RB-13A	115 / 60	Right-Hand Hinge	Black Solid (Lock)	89 lb
U-29RB-15A	115 / 60	Left-Hand Hinge	Black Solid (Lock)	89 lb
U-29RW-00A	115 / 60	Field Reversible	White Solid	89 lb
U-29RW-13A	115 / 60	Right-Hand Hinge	White Solid (Lock)	89 lb
U-29RW-15A	115 / 60	Left-Hand Hinge	White Solid (Lock)	89 lb

ADA Series • 21" ADA Solid Door Refrigerator

DIMENSIONS

Dimensions shown apply to all finishes.



CABINET CUT-OUT



INSTALLATION NOTES

Cutout includes the additional ¼" width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

SPECIFICATIONS

Model	29R	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	35	
Capacity: Can (12 oz)	48	
Capacity: Volume (cu ft)	3.3	
Control Type	Mechanical Dial	
Dimensions: Product Depth	23" / 584 mm	
Dimensions: Product Height	28 ½" / 724 mm	
Dimensions: Product Width	20 7⁄8" / 530 mm	
Energy Consumption: Avg. Per Year	260 kWh	
ENERGY STAR / CEE RATING	ENERGY STAR / Tier 1	
Panel Thickness	¹ /4" (6.3 mm)	
Panel Dimensions: Height	21 ¹³ / ₃₂ " (544mm)	
Panel Dimensions: Width	19 ¹³ / ₁₆ " (503mm)	
Product Weight: Max	80 lb	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	No	
Temperature Range	34°F - 45°F	
h	· · · · · · · · · · · · · · · · · · ·	

COOLING SYSTEM



ELECTRICAL REQUIREMENTS

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).



Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.